

# CALRAD

## 75 Series - Video RF Connectors

### BNC CONNECTORS & ADAPTERS . . . continued

Please Note: For 75-533-PS & 75-534-PS Series, images and specifications are subject to change



**Right Angle Water Resistant Compression Style Connectors Nickel Version**  
 75-533-PSBNCRA RG59  
 75-534-PS-BNCRA RG-6 Gold Version  
 75-533G-PSBNCRA RG59  
 75-534G-PSBNCRA RG-6



**Water Resistant Compression Style Connectors Nickel Version**  
 75-533-PS-BNC RG59  
 75-534-PS-BNC RG-6 Gold Version  
 75-533G-PS-BNC RG59  
 75-534G-PS-BNC RG-6  
 75-534Q-PS-BNC Quad Shield RG-6 Version



**75-645**  
 50 Ohm BNC Female inline connector for RG-59. 3 piece crimp.



**75-646**  
 RG-59 crimp BNC Female 2 piece.



**75-566**  
 Inline BNC Female solderless screw on adapter for RG-58.



**75-559-75**  
 75 ohm version  
**75-559**  
 50 ohm version Solderless BNC Male right angle connector for use with RG-59 coax cable. Cable opening .24". Black snap style plastic body.



**75-559-ST-75**  
 75 ohm version  
**75-559-ST**  
 50 ohm version Solderless BNC Male connector for use with RG-59 coax cable. Cable opening .24". Black snap style plastic body.



**75-554**  
 BNC right angle crimp connector for RG-58. 2 pcs.



**75-561**  
 BNC Male to BNC Female right angle adapter.  
**75-693**  
 75 ohm version.



**75-526**  
 BNC Female to "F" Female.



**75-527**  
 BNC Male to "F" Male.



**75-517**  
 "F" Female to BNC Male adapter.  
**75-517G**  
 Gold version.  
**75-679**  
 75 ohm version.



**75-540**  
 "T" adapter, 2 BNC Females to 1 BNC Male.  
**75-690**  
 75 ohm version.



**75-541**  
 BNC "T" with 3 Female BNC connectors.  
**75-691**  
 75 ohm version.



**75-620**  
 4-way BNC "T" Connector, with 3 Females to 1 Male.




**75-621**  
 3-way BNC "T" BNC Male connectors.



**75-622**  
 3-way BNC "T" Connector, with 2 Males to 1 Female.



**75-623**  
 BNC "T" Connector, with 1 Male to 2 Females.



**75-624**  
 BNC "U" adapter, with 1 Male to 2 Females. U shape.



**75-628**  
 Isolated BNC feed thru. True 75 ohm. Overall length 1.29". Mounts in .5" D hole.  
**75-628-50**  
 50 Ohm Version



**75-552**  
 BNC feed thru double Female panel mount. Mounts in .5" D hole. Overall length is 1.28". Bushing length .33".  
**75-696**  
 75 ohm version



**75-521**  
 Panel feed thru connector. BNC Female to RCA Female. Bushing dia.: .487". Bushing length: .33". Overall length is 1.29". Mounts in .5" hole. 75 ohm.  
**75-521-50**  
 50 Ohm version



**75-543**  
 BNC Female chassis connector. Overall length is 1.08". Mounts in .375" chassis hole. Bushing length .28".  
**75-543G**  
 Gold version.  
**75-697**  
 75 ohm version.



**75-521-3/8**  
 Panel feed thru connector. BNC Female to RCA Female. Bushing dia.: .365". Bushing length: .27". Overall length is 1.06". Mounts in .375" hole.