



GE  
Lighting

**SAFETY & PERFORMANCE**

- ☞ cUL\_Listed
- ☞ FCC\_CS\_NCons
- ☞ NR\_Can
- ☞ UL\_Cls\_P
- ☞ UL\_Listed
- ☞ UL\_Type1\_Out
- ☞ UL\_Type\_CC
- ☞ UL\_Type\_HL
- ☞ NEMA\_Pre

**72266 - GELFL UltraMax™ Professional Series Electronic High Efficiency Multivolt Instant Start Ballast**

**GE232MAX-N/ULTRA**

- ☞ Energy saving high efficiency instant start electronic ballast (> 90%)
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ UL Type CC Rating provides protection against arcing in electrical devices.
- ☞ Anti-Striation Control for better light quality, with no striations.
- ☞ Cold temperature -20F Minimum Starting Temperature

**Product Photo**



**CAUTIONS & WARNINGS**

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

**SPECIFICATIONS BY LAMP & WATTAGE**

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (≥)	Crest Factor (≤)	THD% (≤)	Min. Starting Temp (F/ C)
F17T8	1	120	19	0.16	0.92	5	0.99	1.5	9	-22
F17T8	1	277	19	0.08	0.92	5	0.87	1.5	16	-22
F17T8	2	120	32	0.27	0.92	3	0.99	1.5	7	-22
F17T8	2	277	32	0.12	0.92	3	0.96	1.5	13	-22
F25T12	1	277	27	0.1	0.93	3	0.95	1.5	13	0
F25T12	1	120	26	0.22	0.93	4	0.99	1.5	7	0
F25T12	2	120	48	0.4	0.93	2	0.99	1.5	5	0
F25T12	2	277	47	0.17	0.93	2	0.98	1.5	9	0
F25T8	1	120	25	0.21	0.93	4	0.99	1.5	8	-22
F25T8	1	277	26	0.98	0.93	4	0.94	1.5	13	-22
F25T8	2	120	45	0.38	0.93	2	0.99	1.5	6	-22
F25T8	2	277	45	0.16	0.93	2	0.98	1.5	10	-22
F28T8	2	120	48	0.4	0.85	2	0.99	1.5	4	60
F28T8	1	277	27	0.11	1.05	3	0.95	1.5	13	60
F28T8	1	120	27	0.23	1.05	3	0.99	1.5	7	60
F28T8	2	277	47	0.17	0.85	2	0.98	1.5	8	60
F32T8/WM	1	120	29	0.24	0.88	3	0.99	1.5	7	60
F32T8/WM	1	277	30	0.11	0.88	3	0.96	1.5	12	60
F32T8/WM	2	120	53	0.45	0.88	2	0.99	1.5	5	60

F32T8/WM	2	277	52	0.19	0.88	2	0.99	1.5	8	60
F32T8	2	120	54	0.47	0.88	2	0.99	1.5	5	-22
F32T8	1	120	31	0.26	0.87	3	0.99	1.5	7	-22
F32T8	2	277	53	0.2	0.88	2	0.99	1.5	8	-22
F32T8	1	277	31	0.12	0.87	3	0.96	1.5	12	-22
FE15T8	1	120	15	0.13	0.91	6	0.99	1.5	11	-22
FE15T8	1	277	16	0.08	0.91	6	0.78	1.5	40	-22
FE15T8	2	120	25	0.21	0.91	4	0.99	1.5	8	-22
FE15T8	2	277	25	0.97	0.91	4	0.95	1.5	16	-22
F32T8/25W	1	277	25	0.0	0.87	3	0.97	1.5	10	60
F25T8/WM	1	120	21	0.18	0.84	4	1.0	1.5	8	-22
F25T8/WM	1	277	21	0.09	0.84	4	0.93	1.5	13	-22
F32T8/25W	2	277	43	0.0	0.87	2	0.98	1.5	10	60
F17T8/WM	1	120	16	0.14	0.84	5	0.99	1.5	9	-22
F17T8/WM	2	120	26	0.22	0.85	3	1.0	1.5	7	-22
F17T8/WM	1	277	17	0.08	0.84	5	0.8	1.5	16	-22
F17T8/WM	2	277	26	0.1	0.85	3	0.95	1.5	13	-22
F25T8/WM	2	120	36	0.3	0.85	2	1.0	1.5	6	-22
F25T8/WM	2	277	36	0.14	0.85	2	0.97	1.5	10	-22
F29T8	2	120	48	0.41	0.81		1.0			
F29T8	1	120	30	0.25	0.81		1.0			
F29T8	2	277	47	0.18	0.81		0.98			
F29T8	1	277	30	0.11	0.81		0.96			
F31T8	2	120	51	0.43	0.8		1.0			
F31T8	1	120	29	0.24	0.8		1.0			
F31T8	2	277	50	0.18	0.8		0.98			
F31T8	1	277	29	0.11	0.79		0.95			
F26T8	2	120	44	0.37	0.8		1.0			
F26T8	1	120	26	0.22	0.8		1.0			
F26T8	2	277	43	0.16	0.8		0.98			
F26T8	1	277	26	0.1	0.8		0.95			

Jun 1, 2017 5:44:06 PM For additional information, visit [www.gelighting.com](http://www.gelighting.com)