



GE
Lighting

SAFETY & PERFORMANCE

- ☞ cUL_Listed
- ☞ FCC_CS_NCons
- ☞ UL_Cls_P
- ☞ UL_Listed
- ☞ UL_Type1_Out
- ☞ UL_Type_HL
- ☞ NEMA_Pre
- ☞ Pro_comp_res_req

74463 - GE UltraMax® General Series T8 Electronic Multivolt

Instant Start Ballast

GE432MAX-G-N (Replaces GE-432-MV-N)

- ☞ High performance electronic ballast for all general fluorescent applications
- ☞ Instant start electronic ballast for long lamp starting cycles and low initial cost
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Light-weight, Low Profile Housing
- ☞ Parallel lamp operation means system maintenance is easier to manage
- ☞ Anti-striation Control for better light quality, with no striations

Product Photo



CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (≥)	Crest Factor (≤)	THD% (≤)	Min. Starting Temp (F/ C)
F25T8	4	120	87	0.77	0.87	1	0.99	1.7	10	0
F25T8	3	120	72	0.64	0.93	1	0.99	1.7	10	0
F17T8	3	120	50	0.45	0.91	2	0.99	1.7	10	0
F17T8	3	277	51	0.2	0.91	2	0.97	1.7	10	0
F17T8	4	120	60	0.53	0.87	1	0.99	1.7	10	0
F17T8	4	277	60	0.23	0.87	1	0.97	1.7	10	0
F25T8	3	277	71	0.28	0.93	1	0.98	1.7	10	0
F25T8	4	277	86	0.34	0.87	1	0.98	1.7	10	0
F28T8	3	120	76	0.68	0.85	1	0.99	1.7	10	60
F28T8	3	277	76	0.3	0.85	1	0.98	1.7	10	60
F28T8	4	120	93	0.83	0.82	1	0.99	1.7	10	60
F28T8	4	277	92	0.36	0.82	1	0.98	1.7	10	60
F32T8	3	120	93	0.83	0.93	1	0.99	1.7	10	0
F32T8	3	277	91	0.36	0.93	1	0.98	1.7	10	0
F32T8	4	120	113	0.99	0.88	1	0.99	1.7	10	0
F32T8	4	277	110	0.43	0.88	1	0.98	1.7	10	0
F32T8/25W	3	120	73	0.0	0.85	1	0.99		10	60

F32T8/25W	4	120	88	0.0	0.8	1	0.99		10	60
F32T8/25W	3	277	73	0.0	0.85	1	0.97		16	60
F32T8/25W	4	277	87	0.0	0.8	1	0.98		15	60
F32T8/WM	3	120	86	0.77	0.91	1	0.99	1.7	10	60
F32T8/WM	3	277	86	0.33	0.91	1	0.98	1.7	10	60
F32T8/WM	4	120	103	0.9	0.83	1	0.99	1.7	10	60
F32T8/WM	4	277	103	0.4	0.83	1	0.98	1.7	10	60
F40T8	3	120	112	0.99			0.99	1.7	10	0
F40T8	3	277	110	0.43			0.98	1.7	10	0

Jun 1, 2017 5:44:45 PM For additional information, visit www.gelighting.com