



GE
Lighting

SAFETY & PERFORMANCE

- ☞ cUL_Listed
- ☞ FCC_CS_NCons
- ☞ UL_Cls_P
- ☞ UL_Listed
- ☞ UL_Type1_Out
- ☞ UL_Type_CC
- ☞ UL_Type_HL
- ☞ Meets_2002
- ☞ Meets_1991

71723 - GELFL UltraMax™ Electronic High Efficiency Multivolt

Instant Start Ballast

GE432MAXP-H/ULTRA

- ☞ Energy saving high efficiency instant start electronic ballast (> 90%)
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ UL Type CC Rating provides protection against arcing in electrical devices.
- ☞ Anti-Striation Control for better light quality, with no striations.
- ☞ UL 55C Ambient Rating - High Temperature Protection Circuit
- ☞ Cold temperature -20F Minimum Starting Temperature

Product Photo



CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (≥=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F17T8	3	120	62	0.57	1.25	2	0.99	1.4	10	-22
F25T8	3	120	101	0.87	1.27	1	0.99	1.4	10	-22
F25T8	4	120	121	1.06	1.16	1	0.99	1.4	10	-22
F17T8	3	277	62	0.27	1.25	2	0.95	1.4	21	-22
F17T8	4	120	79	0.62	1.16	1	0.99	1.4	10	-22
F17T8	4	277	78	0.31	1.16	1	0.96	1.4	10	-22
F25T12	3	277	100	0.39	1.22	1	0.97	1.4	17	0
F25T12	3	120	101	0.9	1.22	1	0.99	1.4	10	0
F25T12	4	120	125	1.1	1.11	1	0.99	1.4	10	0
F25T12	4	277	122	0.47	1.11	1	0.97	1.4	14	0
F25T8	3	277	100	0.38	1.27	1	0.96	1.4	17	-22
F25T8	4	277	119	0.45	1.16	1	0.97	1.4	10	-22
F28T8	3	120	105	0.91	1.24	1	0.99	1.4	10	50
F28T8	3	277	102	0.4	1.24	1	0.97	1.4	16	50
F28T8	4	120	127	1.1	1.18	1	0.99	1.4	10	50
F28T8	4	277	125	0.48	1.18	1	0.98	1.4	10	50
F32T8	3	277	117	0.46	1.28	1	0.97	1.4	15	-22
F32T8	3	120	119	1.07	1.28	1	0.99	1.4	10	-22

F32T8	4	120	148	1.3	1.18	1	0.99	1.4	10	-22
F32T8	4	277	145	0.55	1.18	1	0.98	1.4	10	-22
F32T8/25W	3	277	95		1.24	1	0.97	1.4	10	60
F32T8/25W	4	277	116		1.18	1	0.98	1.4	10	60
F32T8/WM	3	277	112	0.41	1.25	1	0.97	1.4	16	50
F32T8/WM	3	120	113	0.99	1.25	1	0.99	1.4	10	50
F32T8/WM	4	120	139	1.21	1.18	1	0.99	1.4	10	50
F32T8/WM	4	277	136	0.51	1.18	1	0.97	1.4	10	50
F40T8	3	120	146	1.27	1.22	1	0.99	1.4	10	-22
F40T8	3	277	142	0.54	1.22	1	0.97	1.4	14	-22
FE15T8	3	277	52	0.22	1.12	2	0.92	1.4	20	0
FE15T8	3	120	51	0.45	1.12	2	0.99	1.4	10	0
FE15T8	4	120	62	0.54	1.03	2	0.99	1.4	10	0
FE15T8	4	277	62	0.26	1.03	2	0.95	1.4	20	0
F25T8/WM	4	120	95	0.8	1.13	1	1.0	1.4	10	-22
F25T8/WM	4	277	94	0.36	1.13	1	0.95	1.4	10	-22
F17T8/WM	4	120	67	0.56	1.14	1	1.0	1.4	10	-22
F17T8/WM	4	277	67	0.28	1.14	1	0.88	1.4	10	-22
F25T8/WM	3	120	79	0.67	1.26	1	1.0	1.4	10	-22
F25T8/WM	3	277	78	0.31	1.26	1	0.92	1.4	17	-22
F17T8/WM	3	277	56	0.24	1.26	2	0.84	1.4	21	-22
F17T8/WM	3	120	56	0.47	1.26	2	0.99	1.4	10	-22
F29T8	3	277	106	0.4	1.24		0.96			
F29T8	3	120	108	0.9	1.24		1.0			
F29T8	4	277	128	0.48	1.14		0.97			
F31T8	3	120	116	0.97	1.26		1.0			
F31T8	3	277	114	0.43	1.26		0.96			
F29T8	4	120	131	1.1	1.14		1.0			
F31T8	4	120	140	1.16	1.06		1.0			
F31T8	4	277	137	0.51	1.13		0.97			
F26T8	3	120	96	0.81	1.19		1.0			
F26T8	3	277	96	0.37	1.19		0.95			
F26T8	4	120	117	0.98	1.09		1.0			
F26T8	4	277	115	0.43	1.09		0.96			