

PW-100 Passive Infrared Wall Switch Occupancy Sensor

High sensitivity and dense coverage for exceptional performance

No neutral wire required

Color-matched lens and • • • • • low profile for appealing design



Selectable operation, walk-through, test and presentation modes for increased energy savings and convenience

Defaults to Manual-ON operation for maximum energy savings

PROJECT

LOCATION/TYPE

Product Overview

Description

The PW-100 passive infrared (PIR) wall switch sensor can turn lights OFF and ON based on occupancy. It is characterized by high sensitivity to small and large movements, appealing aesthetics, and a variety of features.

Operation

The PW-100 replaces existing wall switches and fits in a single gang junction box. It uses advanced PIR technology to detect occupancy and keep lighting ON when it is needed. Once the space is vacated and the time delay elapses, lights automatically turn OFF. DIP switch settings allow for a variety of control options such as Auto-ON operation, walk-through and test modes.

Manual-on Control

Factory default operation is for Manual-ON, so that users turn lights on only when needed. This control strategy is proven to save more energy than Auto-ON, and is in ASHRAE 90.1-2010. If desired, the PW-100 may be reconfigured to turn lights on automatically.

Applications

The PW-100 sensor is well suited for small, enclosed spaces with clear line of sight of the occupant. Common applications include small office, small conference room and lunch/break rooms.

Features

- Detection Signature Processing eliminates false triggers and provides immunity to RFI and EMI
- Zero-crossing for long relay life
- Vandal resistant lens combines precise coverage with durability
- Choice of Manual-ON or Auto-ON operation
- Selectable walk-through mode turns lights off three minutes after the room is initially occupied if no motion is detected after the first 30 seconds
- Test mode allows quick and easy adjustments
- Selectable audible and/or visual alerts for impending shutoff

- In automatic mode, sensor returns automatically to Auto-ON after lights are turned off manually; ideal for presentations
- LED indicates occupancy detection
- Optional light level sensing with simple setup
- Service mode allows sensor to operate as a service switch in the unlikely event of a failure
- Sensor coverage tested to NEMA Guide Publication WD 7-2000
- Compatible with decorator wall plates
- Qualifies for ARRA-funded public works projects




Specifications

Controls &


Settings

- PW-100: 120/277 VAC; 50/60 Hz @ 120 VAC, 0-800 W ballast or tungsten, 1/6 hp @ 277 VAC, 0-1200 W ballast
- PW-100-347: 347 VAC; 50/60Hz; 0-1500 W
- Time delays: 5, 10, 15, 20, 25 or 30 minutes, walkthrough, test-mode
- Coverage: Major motion 35' x 30' Minor motion 20' x 15'
- Sensitivity adjustment: PIR (high/low)
- Dimensions: 2.73" x 1.76" x 1.83" (69.3mm x 44.7mm x 46.5mm) L x W x D
- UL and cUL listed
- Five year warranty

Product Controls




DIP Switch Settings




Coverage & Wiring

Coverage Pattern



Wiring Diagrams



For best performance, WattStopper recommends using this sensor in spaces no larger than $15' \times 12'$.

Ordering Information

Catalog No.	Color	Voltage	Load Rating
PW-100-W PW-100-W-U	White	120/277 VAC; 50/60 Hz 2-wire sensor; no neutral	ଉ 120 VAC, 0-800 W ballast or tungsten,1/6 hp ଉ 277 VAC, 0-1200 W ballast
☐ PW-100-LA	Lt. Almond	connection	
PW-100-I PW-100-I-U	lvory		
PW-100-G	Grey		
☐ PW-100-B	Black		
PW-100-347-W	White	347 VAC; 50/60 Hz	0-1500 W ballast
PW-100-347-LA	Lt. Almond	2-wire sensor; no neutral	
PW-100-347-I	lvory	connection	
PW-100-347-G	Grey		
PW-100-347-B	Black		

Order wall plate separately.

-U = ARRA compliant. Product produced in the U.S.