# ABB contact for Canada/iew.. Print to Pdf..

# CR-U024DC2

#### **General Information**

Extended Product Type: CR-U024DC2

**Product ID:** 1SVR405621R1000 **EAN:** 4013614498374

Catalog Description:CR-U024DC2 Pluggable interface relayLong Description:The CR-U024DC2 pluggable interface relay

is from the CR-U (universal) relay range. This relay operates with a 24 V DC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories.



# **Categories**

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

### **Ordering**

**EAN**: 4013614498374

Minimum Order Quantity: 10 piece
Customs Tariff Number: 85364900

#### **Dimensions**

Product Net Width:35.0 mmProduct Net Height:54.4 mmProduct Net Depth:35.0 mmProduct Net Weight:0.083 kg

#### **Container Information**

Package Level 1 Units: 10 piece
Package Level 1 Width: 182.0 mm
Package Level 1 Height: 76.0 mm
Package Level 1 Length: 77.0 mm
Package Level 1 Gross Weight: 0.870 kg
Package Level 1 EAN: 4013614374012

#### **Technical**

**Function:** Pluggable universal interface relay CR-U

Sub-Function:Relay w/o built in LEDOutput:2 c/o (SPDT) contacts

Output Signal: 250 V / 10 ARated Control Supply Voltage (U<sub>s</sub>): 24 V DC

# **Environmental**

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

# **Certificates and Declarations (Document Number)**

**CCC Certificate:** CCC 2012010303554029

CSA Certificate: CSA\_1587291

Declaration of Conformity - CE: 1SAD938500-0159

GOST Certificate: GOST\_POCC\_DE.AB76.D02256

 LR Certificate:
 LR\_05\_20002\_E2

 RMRS Certificate:
 RMRS\_12.04008.250

 RoHS Information:
 1SAA981040-4403

 UR Certificate:
 UR\_E244330

 VDE Certificate:
 VDE\_40019116

# **Classifications**

**Object Classification Code:** K

**E-nummer:** 4005412

**ETIM 4.0:** EC001437 - Switching relay **ETIM 5.0:** EC001437 - Switching relay

**UNSPSC**: 39121500