

CR-U024DC3



Products Low Voltage Products and Systems Control Products Electronic Relays and Controls
Interface Relays and Optocouplers

General Information

Extended Product Type:	CR-U024DC3
Product ID:	1SVR405622R1000
EAN:	4013614498572
Catalog Description:	CR-U024DC3 Pluggable interface relay 3c/o, A1-A2=24VDC, 250V/10A
Long Description:	The CR-U024DC3 pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 24 V DC rated control supply voltage and has 3 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories.

Additional Information

CCC Certificate:	CCC_2017010303949759
CSA Certificate:	CSA_1587291
Contact Material:	silver-nickel alloy (AgNi)
Country of Origin:	Poland (PL)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC117003D0205
Declaration of Conformity - CE:	1SVD982021-0001
Degree of Protection:	IP40
E-nummer:	4005422
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
EAN:	4013614498572
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
ETIM 6:	EC001437 - Switching relay
Environmental Information:	1SAA981009-2401
Function:	Pluggable universal interface relay CR-U
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SVC405600M9000
Integrated Free-Wheeling Diode:	No
Interface Relay Type:	Pluggable Universal
Invoice Description:	CR-U024DC3 Pluggable interface relay 3c/o, A1-A2=24VDC, 250V/10A
LR Certificate:	LR_05_20002_E3
Manual Operation:	Yes
Maximum Switching Voltage:	250 V
Minimum Order Quantity:	10 piece
Number of Contacts CO:	3
Number of Contacts NC:	0
Number of Contacts NO:	0
Number of LEDs:	0
Object Classification Code:	K
Output:	3 c/o (SPDT) contacts
Output Current:	10 A

Output Signal:	250 V / 10 A
Package Level 1 EAN:	4013614374197
Package Level 1 Gross Weight:	0.87 kg
Package Level 1 Height:	76 mm
Package Level 1 Length:	77 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	182 mm
Power Loss:	Approximately 5 W
Product Main Type:	CR-U
Product Name:	Pluggable Interface Relay
Product Net Depth:	35 mm
Product Net Height:	54.4 mm
Product Net Weight:	0.083 kg
Product Net Width:	35 mm
RMRS Certificate:	RMRS_1740019250
Rated Control Supply Voltage (U _s):	24 V DC
Rated Operational Current (I _o):	10 A
Regulatory Compliance Mark (RCM):	No
RoHS Date:	1146
RoHS Information:	1SVD982021-0001
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CR-U024DC3 Pluggable interface relay
Standards:	EN 50581 IEC/EN 61810-1 UL 508 CAN/CSA C22.2 No.14
Sub-Function:	Relay w/o built in LED
UNSPSC:	39121500
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40019116
eClass:	7.0 27371601