



RESIDENTIAL ELECTRIC PROMAX® STANDARD



Enhanced Heating Elements

- Dual 4500 watt elements for the fastest recovery and reliable operation.
- Incoloy stainless steel lower element lasts longer than standard copper elements.

High Energy Factors

Dynaclean™ Diffuser Dip Tube

Coregard™ Anode Rod

Code Compliance

- Meets UBC, CEC and HUD National Codes.
- Meets the thermal efficiency and standby loss requirements of the U.S. Department of Energy and current edition of ASHRAE/IESNA 90.1.
- Complies with the Federal Energy Conservation Standards effective April 16, 2015, in accordance with the Energy Policy and Conservation Act (EPCA), as amended.

Approved for Manufactured Housing



- All residential electric water heaters are compliant with HUD standards for mobile homes/manufactured housing.

Design-Listed by Underwriters Laboratories

- Certified at 300 PSI test pressure and 150 PSI working pressure.
- Listed according to UL 174 standards governing storage tank-type electric water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Gallon Capacity	First Hour Rating Gallon	Energy Factor	Recovery @ 90°F Rise Gallon Per Hour	Approx. Shipping Weight (lbs)
Tall Models					
ENT-30†	30	47	0.95	21	95
ENT-40†	40	51	0.95	21	118
ENTB-50*	50	70	0.95	21	131
ENT-50†	50	71	0.95	21	134
ENT-55†	55	76	0.94	21	145
Short Models					
ENSB-30*	30	48	0.95	21	95
ENS-30†	30	49	0.95	21	94
ENS-40†	40	55	0.95	21	109
ENS-50†	50	62	0.95	21	161
Lowboy Top Connect Models					
ENL-20	19.5	N/A	N/A	21	65
ENLB-30*	28	40	0.95	21	96
ENL-30†	28	43	0.95	21	115
ENLB-40*	38	46	0.95	21	118
ENL-40†+	38	44	0.95	21	118

Model Number	Element Wattage 240V		Dimensions in Inches		
	Standard	Maximum	A	B	C
Tall Models					
ENT-30†	4500	6000	46-1/2	39-1/2	19
ENT-40†	4500	6000	60-1/4	53-1/4	20
ENTB-50*	4500	6000	60-1/4	51-1/4	21
ENT-50†	4500	6000	60-1/2	51-1/4	22
ENT-55†	4500	6000	56-1/2	48-1/2	24
Short Models					
ENSB-30*	4500	6000	39	30-1/2	20
ENS-30†	4500	6000	39-3/4	30-1/2	22
ENS-40†	4500	6000	50	40-3/4	22
ENS-50†	4500	6000	49-3/4	40-3/8	24
Lowboy Top Connect Models					
ENL-20	4500	N/A	30	21-1/4	20
ENLB-30*	4500	6000	30	21-3/4	22
ENL-30†	4500	6000	31-1/4	21-3/4	24
ENLB-40*	4500	6000	31-3/4	24	24
ENL-40†+	4500	6000	33-1/2	24	26

* Models ship with supplied insulation blanket.

† For 10-year tank and 6-year parts warranty, change "E" to "P" in the model number (example: ENT-30 becomes PNT).

+ Top T&P option not available on this model.

¾" water connections on 8" center.

ENL-20 is a single element configuration only