

- S = SOCKET, SPG = SPIGOT, MPT = MALE PIPE THREAD, FPT = FEMALE PIPE THREAD
- ALL DIMENSIONS ARE IN INCHES.

TOLERANCES


- S = (SOCKET LENGTH) MINIMUM
- G = (LAYING LENGTH) INTERSECTION OF CENTER LINES TO BOTTOM OF SOCKET/THREAD, 90° ELBOWS, TEES, CROSSES, $\pm 1/32''$
- H = INTERSECTION OF CENTER LINES TO FACE OF FITTINGS; 90° ELBOWS, TEES, CROSSES, $\pm 1/32''$
- J = (LAYING LENGTH) INTERSECTION OF CENTER LINES TO BOTTOM OF SOCKET/THREAD; 45° ELBOWS, $\pm 1/32''$
- L = OVERALL LENGTH OF FITTINGS, (INCLUDING CAPS), $\pm 1/16''$
- M = OUTSIDE DIAMETER OF SOCKET/THREAD HUB, $\pm 1/16''$
- N = SOCKET/THREAD BOTTOM TO SOCKET/THREAD BOTTOM; COUPLINGS, $\pm 1/16''$

- DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTIFICATION.

Tee

SxSxS

PVC PART NO. 8400



Size	Universal Part Number	L	H	G	Approx Wt. (Lbs.)
1/2	801-005	2 ¹⁵ / ₁₆	1 ¹⁵ / ₃₂	1 ⁹ / ₃₂	0.11
3/4	801-007	3 ⁷ / ₁₆	1 ²³ / ₃₂	1 ¹ / ₁₆	0.17
1	801-010	4	2	2 ⁷ / ₃₂	0.29
1 1/4	801-012	4 ⁹ / ₁₆	2 ⁹ / ₃₂	1	0.42
1 1/2	801-015	4 ⁷ / ₈	2 ⁷ / ₁₆	1 ¹ / ₃₂	0.51
2	801-020	5 ³ / ₄	2 ⁷ / ₈	1 ⁵ / ₁₆	0.84
2 1/2	801-025	6 ¹⁵ / ₁₆	3 ¹⁵ / ₃₂	1 ²¹ / ₃₂	1.49
3	801-030	7 ¹ / ₂	3 ³ / ₄	1 ²⁷ / ₃₂	2.38
4	801-040	9 ³ / ₈	4 ¹¹ / ₁₆	2 ⁷ / ₁₆	3.76
6	801-060	14 ¹ / ₈	7 ¹ / ₁₆	4 ¹ / ₃₂	10.75
8	801-080	17 ¹⁹ / ₃₂	8 ¹³ / ₁₆	4 ³ / ₄	20.13