



THE OBSERVER 200

INDOOR HIGH WATER ALARM WITH BATTERY BACK-UP

- Red “alarm” light, green “on” light and 85 decibel horn at 10 feet
- Mechanical alarm float switch included (15' cord)
- Alarm test and horn silence button with auto reset – 120 VAC
- The alarm will continue to work even when the primary power fails due to our battery back-up feature
- Auxiliary dry contacts are standard
- External quick connect terminal block for easy float installation
- Two-year limited warranty

SPECIFICATIONS

Dimensions:

6" x 3-3/4" x 2-1/2"

Enclosure:

NEMA 1 thermoplastic (external mounting feet)

Horn:

85 db at 10'

Weight:

2.5 lbs. with float

Voltage:

120 VAC primary, 9 VAC secondary, 60 Hz (alarm condition 2.5 watts max)

Power Cord:

6 feet, 120 VAC

Float Switch:

15' mechanical float with tie strap (normally open)

Float Switch Connection:

Quick connect float connection only. Do not apply power. Class two output, 12 VAC

Standard Auxiliary Contacts:

240 VAC, 5 amp max resistive/ 60 Hz



**Two Year
Limited
Warranty
Included!**



Quick Connect

PART NUMBER	MODEL NUMBER	SUPPLY VOLTAGE	DESCRIPTION	NEMA RATING	SHIPPING WEIGHT	SUGGESTED LIST PRICE
10A200	SMD-21H	120	Indoor alarm with audible and visual alarm, 15' mechanical alarm float, battery back-up, 6' power cord, auxiliary dry contacts, and quick snap terminal connections (High Level)	1	4.0 lbs.	\$112.11
10A202	SMD-21N	120	Indoor alarm with audible and visual alarm, battery back-up, 6' power cord, auxiliary dry contacts, and quick snap terminal connections (No Float Switch)	1	2.0 lbs.	\$90.63
10A204	SMD-21HM	120	Indoor alarm with audible and visual alarm, 15' mercury alarm float, battery back-up, 6' power cord, auxiliary dry contacts, and quick snap terminal connections (High Level)	1	4.0 lbs.	\$112.11
10A206	SMD-21HM-PC	120	Indoor alarm with audible and visual alarm, 15' mercury alarm float, battery back-up, 6' power cord, auxiliary dry contacts, SST pipe clamp, and quick snap terminal connections (High Level)	1	4.0 lbs.	\$117.54