M-PILOT SERIES MERCURY CONTROL DUTY SWITCHES



M-PILOT

FEATURES

- Mercury-activated, pilot duty control switches
- Narrow-angle float, not sensitive to rotation
- For use in water and sewage applications
- Available for pump-up and pump-down applications
- 16-gauge, 2-conductor, SJOW water-resistant (CPE) material
- Maximum 5 amps at 120 VAC / 240 VAC
- 10', 15', 20', 30', or 50' cord
- Individually boxed and includes external weight or SST pipe mount assembly
- For use on control panels and alarm circuits only
- III / cIII
- Three-year limited warranty

*Not recommended for use in drinking water applications.

** All floats that are not sold with an external weight are supplied with an SST pipe mount assembly kit.



Model Explanation Key:

 $\label{eq:cord_length} \# = Cord\ Length\ /\ C = Cord\ Duty\ /\ R = Mercury\ /\ D\ or\ U = Pump\ Down\ or\ Pump\ Up$ $PC\ or\ SW = Pipe\ Clamp\ or\ Weight$

PUMP DOWN



PUMP UP



(Designates normally open contacts for emptying)

(Designates normally closed contacts for filling)

Mercury control duty, 10° narrow-angle float switch designed for use on control panels and alarms.

PART Number	MODEL (See explanation above chart)	PART Number	MODEL (See explanation above chart)	CORD LENGTH	VOLTAGE	EXT. WEIGHT	WEIGHT
20A701	10CRDPC	20A703	10CRUPC	10'	120/240	No	1.6 lbs.
20A702	10CRDSW	20A704	10CRUSW	10'	120/240	Yes	2.8 lbs.
20A705	15CRDPC	20A707	15CRUPC	15'	120/240	No	1.9 lbs.
20A706	15CRDSW	20A708	15CRUSW	15'	120/240	Yes	3.3 lbs.
20A709	20CRDPC	20A711	20CRUPC	20'	120/240	No	2.2 lbs.
20A710	20CRDSW	20A712	20CRUSW	20'	120/240	Yes	3.3 lbs.
20A713	30CRDPC	20A715	30CRUPC	30'	120/240	No	2.6 lbs.
20A714	30CRDSW	20A716	30CRUSW	30'	120/240	Yes	3.8 lbs.
20A717	50CRDPC	20A719	50CRUPC	50'	120/240	No	3.5 lbs.
20A718	50CRDSW	20A720	50CRUSW	50'	120/240	Yes	4.7 lbs