# Product data sheet Characteristics

## 8536SAO12V06

NEMA Motor Starter, Type S, nonreversing, Size 00, 9A, 2 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 480 VAC coil, open

#### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

#### Complementary

NEMA Size	00	
Rated Current	9 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	440 V AC 50 Hz 480 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.81 in (172.96 mm)	
Width	3.50 in (88.90 mm)	
Depth	4.22 in (107.19 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

### Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	00785901743453	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.03 lb(US) (1.83 kg)	
Returnability	No	
Country of origin	MX	

## Packing Units

Package 1 Height	4.70 in (11.938 cm)	
Package 1 width	5.90 in (14.986 cm)	
Package 1 Length	8.00 in (20.320 cm)	

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	
	www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	
PVC free	Yes	

#### Contractual warranty

Ochtractaar Warranty		
Warranty	18 months	