

HOMT215215

Quad tandem mini circuit breaker, Homeline, 2 x 2 pole at 15A, 120/240 VAC, 10 kA AIR, plug in mount



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A 15 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2.0
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 14...AWG 8 aluminium/copper)1

Complementary

Height	3.13 in (79.50 mm)
Width	1.97 in (50.04 mm)
Maximum Depth	3.23 in (82.04 mm)
Tightening torque	35.40 lbf.in (4.0 N.m) 0.00...0.01 in ² (2.5...6 mm ²) AWG 14...AWG 8)

Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	00046 - HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	00785901969150
Nbr. of units in pkg.	5
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	3.30 in (8.382 cm)
Package 1 width	2.00 in (5.080 cm)
Package 1 Length	3.30 in (8.382 cm)

Offer Sustainability

REACH Regulation	📄 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant 📄 EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	📄 Yes
China RoHS Regulation	📄 China RoHS Declaration