

## Product data sheet

### Characteristics

# HOMT220220

Quad tandem mini circuit breaker, Homeline, 2 x 2 pole at 20A, 120/240 VAC, 10 kA AIR, plug in mount



### Main

|                              |                                   |
|------------------------------|-----------------------------------|
| Product                      | Miniature circuit-breaker         |
| Range                        | Homeline                          |
| Current Rating               | 20 A<br>20 A                      |
| Certifications               | UL Listed                         |
| Voltage Rating               | 120/240 V AC                      |
| Mounting Type                | Plug-in                           |
| Number of Poles              | 2P                                |
| Short Circuit Current Rating | 10 kA                             |
| Number of Spaces             | 2.0                               |
| Circuit Breaker Type         | Quad tandem                       |
| Ratings                      | HACR rated                        |
| Electrical Connection        | Box lugs                          |
| Wire Size                    | AWG 14...AWG 8 aluminium/copper)1 |

### Complementary

|                   |                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------|
| Height            | 3.13 in (79.50 mm)                                                                            |
| Width             | 1.97 in (50.04 mm)                                                                            |
| Maximum Depth     | 3.23 in (82.04 mm)                                                                            |
| Tightening torque | 35.40 lbf.in (4.0 N.m) 0.00...0.01 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) AWG 14...AWG 8) |

### Environment

|                                       |                |
|---------------------------------------|----------------|
| Ambient air temperature for operation | 104 °F (40 °C) |
|---------------------------------------|----------------|

### Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 00046 - HOM/T 15-30A 1P; 15-60A 2P |
| Discount Schedule     | DE3D                               |
| GTIN                  | 00785901969723                     |
| Nbr. of units in pkg. | 5                                  |
| Package weight(Lbs)   | 1 lb(US) (0.45 kg)                 |
| Returnability         | Yes                                |
| Country of origin     | MX                                 |

### Packing Units

|                  |                    |
|------------------|--------------------|
| Package 1 Height | 3.20 in (8.128 cm) |
| Package 1 width  | 2.00 in (5.080 cm) |
| Package 1 Length | 3.30 in (8.382 cm) |

Offer Sustainability

|                            |                                                 |
|----------------------------|-------------------------------------------------|
| REACH Regulation           | <a href="#">📄 REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                             |
| EU RoHS Directive          | Compliant <a href="#">📄 EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                             |
| Mercury free               | Yes                                             |
| RoHS exemption information | <a href="#">📄 Yes</a>                           |
| China RoHS Regulation      | <a href="#">📄 China RoHS Declaration</a>        |