

TeSys Power

Fuse carriers

Product references - LS type



LS1D323



LS1D32

Fuse carriers



LS1D32



+ LA8D324

For protection of motors or transformers

3-pole basic blocks					
Connection by spring terminals					
Rating	Cartridge fuse size	Number of early break contacts ⁽¹⁾	Single-phase protection device ⁽²⁾	Reference ⁽³⁾	Weight kg
25 A	10 x 38	— ⁽⁴⁾	Without	LS1D323	0.270
Connection by screw clamp terminals or connectors					
32 A	10 x 38	— ⁽⁴⁾	Without	LS1D32	0.300

4-pole basic blocks					
Connection by screw clamp terminals or connectors					
32 A	10 x 38	— ⁽⁴⁾	Without	LS1D32 + LA8D324 ⁽⁵⁾	0.300

Fuse carriers for the North American market

25 and 30 A basic blocks: please consult your Regional Sales Office.

- (1) With 1 or 2 early break contacts to be inserted in the contactor control circuit.
- (2) Fuse carriers with single-phase protection device must be fitted with striker fuses.
- (3) LS1D: clips directly onto a 35 mm rail or screw fixing.
- (4) Addition of add-on contact block, see page B4/7.
- (5) Can be mounted on left-hand or right-hand side of the basic block.