QOU125

Mini circuit breaker, QOU, 25A, 1 pole, 120/240 VAC, 10kA





Main

Main	
Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

25 A	
Slotted box lugs, line side	
Slotted box lugs, load side	
120/240 V AC	
120 V AC	
48 V DC	
Unit mount	
AWG 14AWG 2 aluminium/copper	
4.05 in (102.87 mm)	
2.95 in (74.93 mm)	
0.75 in (19.05 mm)	
45 lbf.in (5.08 N.m) AWG 14AWG 2)	
	Slotted box lugs, line side Slotted box lugs, load side 120/240 V AC 120 V AC 48 V DC Unit mount AWG 14AWG 2 aluminium/copper 4.05 in (102.87 mm) 2.95 in (74.93 mm) 0.75 in (19.05 mm)

Environment

Product certifications	UL Listed
	IEC
	CSA

Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901489085
Nbr. of units in pkg.	1
Package weight(Lbs)	0.35 lb(US) (0.16 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	0.90 in (2.286 cm)
Package 1 width	3.10 in (7.874 cm)
Package 1 Length	4.50 in (11.430 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty 18 months	
--------------------	--