# UTH4330T

Individual meter socket, ringless socket, lever bypass, 4 jaws no release, OH, UG, 320 A, up to 600 VAC single phase 3W



Main	
Product or component type	Meter Socket
Meter socket type	Ringless
Hub type	A-L ACPL closing plate

## Complementary

Complementary	
Meter socket rated current	320 A
Number of jaws	4 with jaw release
Bypass type	Lever bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure material	Steel
Box number	11R
Electrical connection	Studs
Service feed location	UG OH
Wiring configuration	3-wire
Device mounting	Surface
Maximum Depth	5.68 in (144.27 mm)
Width	15.00 in (381.00 mm)
Height	36.62 in (930.15 mm)

### Environment

Product certifications	UL Listed	
Enclosure Rating	NEMA 3R	:

#### Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS	
Discount Schedule	DE4	
GTIN	00785901627739	
Package weight(Lbs)	38.44 lb(US) (17.44 kg)	
Returnability	Yes	
Country of origin	US	

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Warranty 18 months

## **Approximate Dimensions**

