


**EMT SET SCREW CONNECTORS****Insulated Set Screw Connector, Steel****B03**

Catalog #: 2128

**APPLICATIONS**

For use in dry locations to bond EMT conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped.

**PRODUCT FEATURES**

All steel construction insures mechanical protection for the raceway  
Tri-head screws may be installed using a slotted, Phillips, or Robertson head screwdriver  
2-1/2 in. to 4 in. trade sizes are also UL listed for use on Rigid/IMC conduit, allowing for design and installation flexibility  
All components are zinc electroplated for corrosion protection  
1/2 in. to 1 in. trade sizes have one set screw, 1-1/4 in. to 4 in. trade sizes have two set screws  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

**UL LISTED**

2-1/2" - 4" Standard 514B, File E195969, E195970

**CULUS**

1/2" - 2" Standard 514B, C22.2 # 18

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings\\_January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings_January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Sub Class: Insulated  
Trade Size: 2 in.

**DRAWING DIMENSIONS**

Dimension A: 2.485"  
Dimension B: 2.235"  
Dimension D: .408"  
Dimension E: 1/4 - 28

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 20  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 56  
Ship Carton Length (in.): 12.88  
Ship Carton Width (in.): 8.75  
Ship Carton Height (in.): 5.63  
Ctn Weight (Lbs.): 11.20  
Pallet Qty: 1800  
UPC Number: 050169021286