



Safety switch, general duty, fusible, 2 pole, 3 wire, 240VAC, 600A, Type 3R, with neutral

D226NR

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Single Throw Safety Switch	
Duty Rating	General duty	
Device Application	Commercial	
Disconnect Type	Fusible disconnect switch	
Factory Installed Neutral	Neutral (factory installed)	
Number of Poles	2	
Current Rating	600 A	
Voltage Rating	240 V AC	
Enclosure Rating NEMA	NEMA 3R	

Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K, J or R	
Fuse type	H, K, J or R	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 4500 kcmil aluminium/copper	
Tightening torque	450 lbf.in (50.8 N.m) (AWG 4500 kcmil)	
Depth	8.88 in (225.55 mm)	
Width	25.13 in (638.30 mm)	
Height	49.13 in (1247.90 mm)	
Net Weight	116.8 lb(US) (53 kg)	

Environment

Certifications UL listed file E2875

Ordering and shipping details

Category	US1DE1A00107
Discount Schedule	DE1A
GTIN	785901460855
Returnability	Yes
Country of origin	MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.01 in (30.5 cm)
Package 1 Width	25.98 in (66.0 cm)
Package 1 Length	51.30 in (130.3 cm)
Package 1 Weight	110.000 lb(US) (49.895 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	1408	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free plastic parts product
Take-back	No