



Meter mains, Homeline, CSED, ringless socket, 200A, surface mount, maximum 8 spaces, 16 circuits, no bypass

RC816F200C

Product availability: Stock - Normally stocked in distribution facility

Main

Bus Rating

Product or Component Type

Range of Product	Homeline	
Complementary		
Line Rated Current	200 A	
Short-circuit current	22 kA	
Network number of phases	1	
Meter socket type	Ringless	
Mounting	Surface	
Number of spaces	8	
Number of circuits	16	
Number of Tandem Breakers	8	
Hub type	A	
Electrical connection	Lugs, line side Feed-thru lugs, service ground	
Wire Size	AWG 6350 kcmil aluminium/copper)line side AWG 12AWG 2/0 aluminium/copper)service ground	
Tightening torque	Main lugs 250 lb.in, AWG 6350 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14AWG 2/0, copper Service ground 50 lb.in, AWG 12AWG 2/0, aluminium Branch lugs 35 lb.in, AWG 6AWG 4, aluminium/copper Branch lugs 25 lb.in, AWG 8, aluminium/copper Branch lugs 20 lb.in, AWG 14AWG 10, copper Branch lugs 20 lb.in, AWG 12AWG 10, aluminium Cover 10 lb.in	
Disconnect	Service disconnect (factory installed)	
Main Breaker Rating	200 A	
Branch Breaker Rating	200 A	
Service feed location	OH UG	
Bypass type	No bypass	
Height	35.13 in (892.30 mm)	
Width	14.37 in (365.00 mm)	
Depth	5.07 in (128.78 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

200.0 A

Environment

Product certifications UL E-6294

Ordering and shipping details

Category	US1DE3A00048	
Discount Schedule	DE3A	
GTIN	785901863922	
Returnability	Yes	
Country of origin	MX	

Packing Units

_		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.75 in (14.61 cm)	
Package 1 Width	14.63 in (37.16 cm)	
Package 1 Length	36.13 in (91.77 cm)	
Package 1 Weight	43.649 lb(US) (19.799 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	21	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 Width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	
Package 2 Weight	897.000 lb(US) (406.872 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	399
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No