## High Efficiency **Series** Water Softener







## Programmable Dealer Contact Display



- LOW SALT REMINDER calculates salt usage and provides a visual and audible reminder to add salt
- MAINTENANCE REMINDER allows installer to set a reminder for customer to perform required scheduled maintenance (visual and audible)

## **Features:**

- True 1" porting provides high flow rates for larger homes
- Upflow Regeneration with Optimal Precision Brining provides high-efficiency performance and lowest possible salt usage.
- Adjustable backwash frequency saves up to 2,000 gallons of water per year
- Large 4 line Touch Pad LCD display. No confusing symbols or codes.
- Automatic reserve adjusts based on actual usage
- Automatic System Flush refreshes system during periods of non-use preventing bacteria growth
- Soft Water Recharge performs quick regeneration ensuring you never run out of soft water
- Soft Water Brine Tank Refill conserves capacity and keeps brine tank clean
- Time saving quick connect features on bypass, drain line and powercord
- Meter immediate; meter delayed; meter override; vacation and calendar clock modes
- Self charging capacitor keeps date / time of day for 48 hours while programming remains in permanent memory
- Space saving bypass with integrated turbine meter
- Ocomes with 1" straight NPT and 1" 90 degree elbows
- NSF certified control valve and pressure tank; IAPMO certified ion exchange resin



Upflow Regeneration drives the hardness minerals up through the already depleted resin and out to drain - saving both salt and the unused portion of the resin for future use.





7 Year Warranty Lifetime Warrant Control Valve Pressure tank

Part #	Model	System Capacity Grains			Flow Rate			Regeneration Water Usage (Gallons)				Brine Tank /	Salt	Ship	
		@ 10 lbs/ cu ft	@ 6 lbs/ cu ft (Factory Setting)	@ 3 lbs/ cu ft	Flow Rate @ 15 psi Pressure Drop		Backwash USGPM	Clean Water (Factory Setting)	Problem Water	Mineral Tank Size	Resin Cu. Ft.	Cabinet Size Inches	Capacity (Lbs)	Weight (Lbs)	
15010660	NVO489UF-075	22,500	18,750	11,250	10.4 gpm	14.3 gpm	1.5	34.0	49.6	8 x 44	0.75	18.1 x 34.7	270	93	
15010661	NVO489UF-100	30,000	25,000	15,000	11.0 gpm	15.0 gpm	2.0	43.4	64.3	9 x 48	1.00	18.1 x 34.7	270	110	
15010662	NVO489UF-150	45,000	37,500	22,500	11.2 gpm	15.1 gpm	2.4	62.7	90.3	10 x 54	1.50	18.1 x 34.7	270	141	
15010663	NVO489UF-200	60,000	50,000	30,000	12.2 gpm	16.2 gpm	3.5	87.1	124.6	12 x 52	2.00	20.3 x 37.4	350	158	
15010664	NVO489UF-300	90,000	75,000	45,000	12.6 gpm	16.6 gpm	5.0	139.2	196.2	14 x 65	3.00	23.0 x 40.5	420	244	
15010693	NVO489UF-100C	30,000	25,000	15,000	12.0 gpm	16.0 gpm	2.4	48.6	69.5	10 x 35	1.00	13.8 x 23.6 x 43.3	225	110	
Regeneration	Counter Current / Upflow														
Plumbing C	Includes 1" 90 Degree Elbows and 1" Straight Connectors														
Resin Type	Aquafine 8% High Capacity Ion Exchange Resin														
Electrical Requirements				Input 120V 60Hz - Output 12V 650mA											
Water Tem	Min. 39 - Max. 100 Degrees Fahrenheit														
Water Press	Min. 20 - Max 125 psi														



IAPMO R & T Certified Against NSF/ANSI 44



Designed, Engineered & Assembled in the U.S.A. Toll Free: 877-288-9888 www.novowater.com

Regina, SK • Cambridge, ON • Whitestown, IN Houston, TX • Phoenix, AZ • Guadalajara, MX

Your Local Plumbing Professional