

FILTER housings

Slim Line®



W38-PRA

W385-PR

- Point-of-Use filter housings
- 3/8-inch NPT inlet/outlet
- 5- and 10-inch lengths
- Pressure relief button
- WMB38 Mounting Bracket included

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W385-PR	152007	Gray	Black	3/8" NPT	4½" x 7"	30-125 psi	40-100°F	WW38
W38-PRA	152005	Gray	Black	3/8" NPT	4½" x 7"	30-125 psi	40-100°F	WW38

Standard



W34-PR

WC34-PR

- Whole-House filter housings
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Clear or opaque sump
- Accepts a wide variety of 2½- to 3-inch diameter cartridges



The WC34-PR is Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W34-PR*	152047	Gray	Black	3/4" NPT	5⅞" x 12¼"	30-125 psi	40-100°F	WMB34, WW34
WC34-PR	152018	Clear	Black	3/4" NPT	5⅞" x 12¼"	30-125 psi	40-100°F	WMB34, WW34

* Not Performance Tested or Certified by NSF

Valve-in-Head



WVC34

- Whole-House filter housing
- Valve-in-Head (VIH) closes both the inlet and outlet port simultaneously, making cartridge change-outs quick and easy
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Accepts a wide variety of 2½- to 3-inch diameter cartridges



Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
WVC34	152003	Clear	Black	3/4" NPT	5⅞" x 12¼"	30-125 psi	40-100°F	WMB34, WW34

†See page 14 for part number and description.
Note: See chart on page 16 for flow rates with specific cartridges.