

FILTER housings

- Point-of-Use filter housings
- Available with 3/8-inch NPT or quick connect inlet/outlet

- Integral mounting bracket
- Pressure relief button



Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W38-PRB	152086	Gray	Black	3/8" NPT	5¼" x 13½"	30-125 psi	40-100°F	WW38
W38-PRQC	152085	Gray	Black	3/8" QC	5¼" x 13½"	30-125 psi	40-100°F	WW38



W38-PRB

W38-PRQC

- Whole-House filter housings
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Integral mounting bracket

- Clear or opaque sump
- Accepts a wide variety of 2½- to 3-inch diameter cartridges



The W34-PRB is Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W34-PRB	152084	Gray	Black	3/4" NPT	5¼" x 12¼"	30-125 psi	40-100°F	WW34
WC34-PRB*	152083	Clear	Black	3/4" NPT	5¼" x 12¼"	30-125 psi	40-100°F	WW34

*Not Performance Tested or Certified by NSF.



WC34-PRB

W34-PRB

- Whole-House filter housing
- Three-color monitor indicates when to change the filter
- 3/4-inch NPT inlet/outlet
- Pressure relief button

- Integral mounting bracket
- Includes WPD-110 5-micron sediment cartridge
- Includes WW34 housing wrench
- Accepts a wide variety of 2½- to 3-inch diameter cartridges

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W34-PRM	152082	Gray	Black	3/4"	5¼" x 15"	30-125 psi	40-100°F	WMB34, WW34



W34-PRM

Monitored Whole-House

†See page 14 for part number and description.
Note: See chart on page 16 for flow rates with specific cartridges.