

INTEGRAL BRACKET SLIM LINE®

- Available with 3/8" NPT or quick connect inlet/outlet
- Integral mounting bracket
- Pressure relief button



Tested and Certified by NSF International.

COMPONENT



W38-PRB

W38-PRQC

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)	Optional Accessories Model #
W38-PRB	152086	Gray	Black	3/8" NPT	5 1/4" x 13 1/2"	30-125	40-100	WW38
W38-PRQC	152085	Gray	Black	3/8" QC	5 1/4" x 13 1/2"	30-125	40-100	WW38

INTEGRAL BRACKET STANDARD

- 3/4" NPT inlet/outlet
- Integral mounting bracket
- Pressure relief button
- Available with either clear or opaque sump
- Accepts a wide variety of 2 1/2" to 3" diameter cartridges



Tested and Certified by NSF International.

COMPONENT



W34-PRB

WC34-PRB

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)	Optional Accessories Model #
W34-PRB	152084	Gray	Black	3/4" NPT	13 1/4" x 5 3/4"	30-125	40-100	WW34
WC34-PRB	152083	Clear	Black	3/4" NPT	13 1/4" x 5 3/4"	30-125	40-100	WW34

MONITORED WHOLE HOUSE

- 3 color monitor indicates when to change cartridge
- Integral mounting bracket
- 3/4" NPT inlet/outlet
- Pressure relief button
- Accepts a wide variety of 2 1/2" to 3" diameter cartridges
- Includes WPD-110, 5 micron sediment cartridge
- Includes WW34 housing wrench



W34-PRM

Available in many sizes and styles, our housings are manufactured from durable materials with proven performance, including polypropylene, and clear styrene acrylonitrile.

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)
W34-PRM	152082	Gray	Black	3/4" NPT	15" x 5 3/4"	30-125	40-100