



## ProLume® High Lumen PLL

**Halco**  
LIGHTING TECHNOLOGIES®

Halco ProLume® High Lumen PLLs provide light output that is comparable to T8 and T5/HO lamps in a more compact lamp design. The versatility of High Lumen PLL lamps makes them a viable option to operate low-profile fixtures in numerous applications. Halco High Lumen PLL lamps use a tri-phosphor coating that provides high color rendering. These TCLP Compliant lamps are available in wattages ranging from 18W to 55W and color temperatures between 3000K and 5000K.

### Specifications

- Up-to 85 LPW
- Minimum starting temperature 14°F
- Flicker-free
- Available in 18W, 24W, 36W, 40W and 55W
- 3000K, 3500K, 4100K and 5000K color temperature options
- 12,000 and 20,000 hours average rated life
- Improved optical control
- 1-Year Limited Warranty

- » Up-to 85 LPW
- » Long life
- » 1-Year Limited Warranty

### Markets:

- Residential
- Commercial

### Applications:

- Office
- Healthcare
- Hospitality
- Retail



## Ordering Information

Watt	Base	Product #	Product Code	Description	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg. Rated Life	Pkg. Qty.	MOL
18 Watt	2G11	109700	PLL18/835/ECO	White, Eco-Shield®	3500	82	1250	1125	12000	10/40	8.94"
18 Watt	2G11	109702	PLL18/841/ECO	Cool White, Eco-Shield®	4100	82	1250	1125	12000	10/40	8.94"
24 Watt	2G11	109704	PLL24/835/ECO	White, Eco-Shield®	3500	82	1800	1620	12000	10/40	12.70"
24 Watt	2G11	109706	PLL24/841/ECO	Cool White, Eco-Shield®	4100	82	1800	1620	12000	10/40	12.70"
36 Watt	2G11	109708	PLL36/835/ECO	White, Eco-Shield®	3500	82	2800	2520	12000	10/40	16.45"
36 Watt	2G11	109710	PLL36/841/ECO	Cool White, Eco-Shield®	4100	82	2800	2520	12000	10/40	16.45"
40 Watt	2G11	109712	PLL40/830/RS/ECO	Soft White, Eco-Shield®	3000	82	3150	2835	20000	10/40	22.50"
40 Watt	2G11	109714	PLL40/835/RS/ECO	White, Eco-Shield®	3500	82	3150	2835	20000	10/40	22.50"
40 Watt	2G11	109716	PLL40/841/RS/ECO	Cool White, Eco-Shield®	4100	82	3150	2835	20000	10/40	22.50"
40 Watt	2G11	44900	PLL40/850/RS/ECO	Natural White, Eco-Shield®	5000	82	3150	2835	20000	10/40	22.50"
55 Watt	2G11	109718	PLL55/835/ECO	White, Eco-Shield®	3500	82	4700	4230	12000	10/40	21.20"
55 Watt	2G11	109720	PLL55/841/ECO	Cool White, Eco-Shield®	4100	82	4700	4230	12000	10/40	21.20"

Eco-Shield® indicates TCLP Compliant lamps.

 Hg—LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.

CAUTION: This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.