



Wall Mount with Photocell

Die-cast aluminum housing with dark bronze powder coated finish.

LED Wall Mount Fixture is designed for safety and security in residential, stairway, storage and perimeter lighting applications. Features a photocell and a powerful LED array for maximum energy efficiency. Die-cast aluminum construction, powder coat finish and a polycarbonate lens combine to make this a beautiful yet durable lighting fixture.

120V

EWM17W30

1600 lm
3000K
17W

EWM25W30

2000 lm
3000K
25W

EWM17W40

1650 lm
4000K
17W

EWM25W40

2100 lm
4000K
25W

120/277V

EWM17W30U

1600 lm
3000K
17W

EWM25W30U

2000 lm
3000K
25W

EWM17W40U

1650 lm
4000K
17W

EWM25W40U

2100 lm
4000K
25W

INPUT VOLTAGE 120V AC or 120/277V AC

WATTAGE 17W (120W Incandescent Equivalent), 25W (50W HID Equivalent)

CRI 80+

LIFE SPAN 50,000 Hours L70

WET LOCATION UL Listed

QUALIFIED DLC

LENS Shatterproof polycarbonate

KNOCKOUTS Side & back access

DRIVER High efficiency (HPF), Class 2


POWER FACTOR 0.9

LM-80 Certified

FINISH Dark Bronze

MOUNT Jbox or wall mount

PHOTOMETRICS Page 11



Product Number Builder

ELCO	Wall Mount	Wattage	Wall	Color Temp	Voltage
E	WM		W		
		17 17W		30 3000K	(blank) 120V
		25 25W		40 4000K	U 120/277V

Example: **EWM17W30U** [ELCO Wall Mount, 17 Watts, 3000K, 120/277V]