

# Accessories



**FIRECVR**  
Fire Cover

Recessed fire cover stops flame spread and heat transmission for up to 2 hours. UL rated. UL approved for most major ceiling types. Made of heat activated intumescent material.



**FIREENCL**  
Fire Enclosure

Flexible mica fire enclosure for recessed fixtures. ETL approved for 1-Hour fire resistance. Easy to install. To be used with Mica Fire Tape (sold separately) to seal the power feeding points. Meets the specifications of UL 263, ASTH E119.



**FIRETAPE**  
Mica Fire Tape

Fire proof mica adhesive tape helps seal the power feeding point on Fire Enclosure (FIREENCL). Offers outstanding high temperature and flame resistance, and provides excellent electrical insulating. Measures 3/4" x 6 1/2'.



**ELJ442** (4"x4"x2 1/8")  
**ELJ443** (4"x4"x3 1/2")  
2-Hour Fire Rated Junction Box

Fire rated junction box constructed from 16 gauge galvanized steel. 2 hour fire rating.



**EP710C** (20° Beam)  
**EP711C** (36° Beam)  
**EP712C** (60° Beam)  
Interchangeables Lens

Interchangeables lens for LED Adjustable Pull-Down Inserts.



**PSA30**  
Socket Adaptor

Socket adaptor E26 to quick connector.



**PSA31**  
Socket Adaptor

Socket adaptor GU10 to quick connector.



**PSA35**  
Socket Adaptor

Socket adaptor GU24 to quick connector.



**MR120-GU10LD**  
LED GU10 Lamp

7W, 500 lm, 3000K, CRI 90, 120V, dimmable.



**PSA34**  
LED Lamp

7W LED COB lamp with medium base socket. 500 lm, 3000K, CRI 90, dimmable, 120V.



**PSA37**  
Quick Connect LED MR16 Lamp

7W LED COB lamp with quick connector. 500 lm, 3000K, CRI 90, dimmable, 120V.