

STEEL DROP-IN ANCHORS



See page 240 for
Stainless Steel.

- Use with machine screw, bolt or threaded rod.
- For use in solid concrete, hard stone and solid block.
- Internally threaded expansion anchor.
- **Requires layout or hole spotting.**

					Gravity Feed Jar		
Thread Size	Length	Thread Depth	Drill/Hole Diameter	Min Embed	Part #	Jar Qty	Master Carton
1/4-20	1	7/8	3/8	1	60402J	100	600
3/8-16	1 9/16	5/8	1/2	1 5/8	60404J	100	600
1/2-13	2	1 3/16	5/8	2	60406J	50	300
5/8-11	2 1/2	1 3/16	7/8	2 1/2	60408J	25	150
3/4-10	3 1/8	1 3/16	1	3 3/16	60410J	25	150
3/8-16	Shallow Embedment Anchors		1/2	3/4	60405J	100	600



Setting Tool
Included!

Setting Tool		
Size	Part #	Qty
1/4	60440	1
3/8	60444	1
1/2	60446	1
5/8	60448	1
3/4	60450	1

Installation

1. Use a masonry bit. Drill the hole to any depth slightly deeper than the anchor length.
2. Clean the hole using pressurized air.
3. Insert the anchor into the hole and hammer the anchor down until it is flush with the surface.
4. Expand the anchor by hitting the setting tool until the shoulder is flush with the anchor.