



Representative Image

Catalog No. U038C010

Description: 100A SURFACE 20/20GFCI/20GFCI

UPC No 784567568615

Products > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Power Outlets & Temporary Power
----------	---------------------------------

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	6-20R, (2) 5-20R2GFCI
Feed	Overhead
AIC	10,000
Amps	100.0 A
Cabinet Size	9 X 17
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB220, (2) CB120
Load Center	LC55N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	15.0 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
Temporary Power Brochure 6 pages. MET-019 Rev. A.	MET-019A	Brochures

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, time current curves, CSI Specifications and promotional literature.