




Quality, efficiency, taken to great lengths.

At Satco we stock an unprecedented variety of fluorescent lamps. Everything from T5 to T12 sizes, including our Hygrade™, Circline and U-bend styles. There are high-output, rapid start, and instant versions sure to fill any commercial or residential application. Our germicidal and other specialty fluorescents complete one of the most extensive selections in the industry. Our fluorescent lamps are energy efficient, manufactured to the highest standards, and we're stocked to ensure quick deliveries, whatever the quantity.

Fluorescent lamp features:

- Available in all standard and high-output wattages from 4 to 215 Watts
 - Superior CRI levels
 - Virtually all industry sizes
 - Manufactured to RoHS standards and Federal TCLP standards
 - CEE listed High Performance and Reduced Wattage options to meet Energy Efficient Commercial Lighting System conversions
 - High lumen maintenance levels
 - Long Life – up to 48,000 hour life*
 - Environmentally friendly – low UV and low Mercury
 - Full range of color temperatures from 2455K to 6500K
 - Lamps for both commercial and residential applications
- * Life dependent on ballast and hours per start



T8
Med. Bi Pin

Standard T8 Lamps

T8 Instant/Rapid Start Lamps* (Electronic Ballast) 24"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
17	T8	Med. Bi Pin	S6520 ▲	F17T8/730/ECO	Warm White	3000	75	24000	1300	24	23 ¾	30	11, 12, 13
			S8404	F17T8/830/ENV	Warm White	3000	85	20000	1450	24	23 ¾	30	11, 12, 13
			S6523 ▲	F17T8/830/ECO	Warm White	3000	82	24000	1400	24	23 ¾	30	11, 12, 13
			S6521 ▲	F17T8/735/ECO	Neutral White	3500	75	24000	1300	24	23 ¾	30	11, 12, 13
			S8405	F17T8/835/ENV	Neutral White	3500	85	20000	1450	24	23 ¾	30	11, 12, 13
			S6524 ▲	F17T8/835/ECO	Neutral White	3500	82	24000	1400	24	23 ¾	30	11, 12, 13
			S6522 ▲	F17T8/741/ECO	Cool White	4100	75	24000	1300	24	23 ¾	30	11, 12, 13
			Shatter Proof S6583 ▲	F17T8/741/TF/ECO	Cool White	4100	75	24000	1300	24	23 ¾	30	9, 11, 12, 13
			S8406	F17T8/841/ENV	Cool White	4100	85	20000	1450	24	23 ¾	30	11, 12, 13
			S6525 ▲	F17T8/841/ECO	Cool White	4100	82	24000	1400	24	23 ¾	30	11, 12, 13
			Shatter Proof S6693 ▲	F17T8/841/TF/ECO	Cool White	4100	82	24000	1400	24	23 ¾	30	11, 12, 13
			S8432	F17T8/850/ENV	Natural Light	5000	82	20000	1400	24	23 ¾	30	11, 12, 13
			S8433	F17T8/865/ENV	Daylight	6500	82	20000	1300	24	23 ¾	30	11, 12, 13

T8 Instant/Rapid Start Lamps* (Electronic Ballast) 36"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
25	T8	Med. Bi Pin	S6526 ▲	F25T8/730/ECO	Warm White	3000	75	24000	2025	36	35 ¾	30	11, 12, 13
			S8410	F25T8/830/ENV	Warm White	3000	85	20000	2300	36	35 ¾	30	11, 12, 13
			S6529 ▲	F25T8/830/ECO	Warm White	3000	82	24000	2150	36	35 ¾	30	11, 12, 13
			S6527 ▲	F25T8/735/ECO	Neutral White	3500	75	24000	2025	36	35 ¾	30	11, 12, 13
			S8411	F25T8/835/ENV	Neutral White	3500	85	20000	2300	36	35 ¾	30	11, 12, 13
			S6530 ▲	F25T8/835/ECO	Neutral White	3500	82	24000	2150	36	35 ¾	30	11, 12, 13
			S6528 ▲	F25T8/741/ECO	Cool White	4100	75	24000	2025	36	35 ¾	30	11, 12, 13
			Shatter Proof S6584 ▲	F25T8/741/TF/ECO	Cool White	4100	75	24000	2025	36	35 ¾	30	9, 11, 12, 13
			S8412	F25T8/841/ENV	Cool White	4100	85	20000	2300	36	35 ¾	30	11, 12, 13
			Shatter Proof S6692 ▲	F25T8/841/TF/ECO	Cool White	4100	82	24000	2150	36	35 ¾	30	11, 12, 13
			S6531 ▲	F25T8/841/ECO	Cool White	4100	82	24000	2150	36	35 ¾	30	11, 12, 13
			S8434	F25T8/850/ENV	Natural Light	5000	82	20000	2200	36	35 ¾	30	11, 12, 13
			S8435	F25T8/865/ENV	Daylight	6500	82	20000	2150	36	35 ¾	30	11, 12, 13

* Shatter Proof is available on all Fluorescent Lamps.