



Catalog Number: U4911-X-BL
Item Description: 320A 7T RL SWY STUD HD
UPC Code: 784572260252

Brand Name: Milbank
Type: Ringless Meter Socket
Application: Meter Socket
Standard: UL Listed
Voltage Rating: 600 Volts Alternating Current
Amperage Rating: 320 Ampere Continuous
Phase: 3 Phase
Frequency Rating: 60 Hertz
Cable Entry: Overhead and Underground
Terminal: 3/8 Inch Stud Line Side and 3/8 Inch Stud Load Side
Mounting: Surface Mount
Enclosure: Type 3R, G90 Galvanized Steel with Powder Coat Finish





Additional Specifications:

- AIC or SCCR Rating: Please Contact Factory
- Optional Line Side Lug Kits: K3082, K3441, K3442
- Optional Load Side Lug Kits: K3082, K3441, K3442
- Maximum Amperage: 400 Maximum Ampere
- Number of Jaws: 7 Terminal
- Hub Opening and Closing Plates: Large Closing Plate
- Equipment Ground: Grounding Stud
- Bypass Provision: Lever Bypass
- Barrel Lock Provision: 9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
- Number Positions: 1 Position

Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

FEATURE TABLE		
ITEM	QTY	DESCRIPTION
A	6	U/L MNTG.EMBOSS
B	1	¼ SOLID K.O.
C	1	½, ¾, 1 CONC. K.O.
D	2	2, 2½, 3 CONC. K.O.
E	2	2, 2½, 3, 3½, 4 CONC. K.O.



Version:

1

All dimensions are +/- 1/16".
Drawing views are not to scale.
Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.