

Search within category

BUY NOW

DESIGN / INSTALL



LAM3B1/0-38-6Y

Two-hole, aluminum, three barrel lug, type LAM3B, NEMA hole sizes and spacing, #12 - 1/0 AWG, 3/8" (9.5mm) stud hole.

LAM3B1/0-38-6Y replaces LAM3B1/0-38-6

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
Note	LAM3B1/0-38-6Y replaces LAM3B1/0-38-6			
Material	Tin-Plated Aluminum			
Copper and Aluminum Conductor Size Range	#14 AWG - 1/0 AWG			
No. of Ports	—			
Stud Hole Size In. (mm)	3/8 (9.525)			
Stud Hole Spacing In. (mm)	1.00 (25.4)			
Height 1 In. (mm)	—			
Height 2 In. (mm)	—			
Height In (mm)	0.88 (16.0)			
Hex Key Size (In.)	**			
Length In (mm)	2.91 (74.7)			
Mounting Hole Spacing In. (mm)	—			
NEMA Hole Spacing	—			
Tongue Length In. (mm)	2.16 (54.9)			
Tongue Thickness In. (mm)	0.25 (6.35)			
Tongue Width In. (mm)	2.00 (50.8)			
Width In (mm)	—			
CSA Certified	C22.2 No. 65-13			
Max. Voltage Rating	—			
Temperature Rating	—			
Tin-Plating Meets ASTM B545-97, Class C	320µ in (8µ m)			
UL Listed	486A-486B File #E52164			
UL Temperature Rating	—			
UL and CSA Temperature Rating	90°C			
UL and CSA Voltage Rating	600V			
Insulation	—			

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote! ▶

Part Number Series	LAM3B1/
Stud Hole Spacing (In.)	1.00
Part Features	The use of Panduit oxide inhibiting joint compound (CMP-100) is recommended for pad to pad and conductor connections
RoHS Compliancy Status	Compliant
Min. Order Qty.	1.0000

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote! ▶