

4" SQUARE SINGLE DEVICE RINGS



52C62A



FEATURES

- Angled slots on the covers compensate for up to 12° of box misalignment on upright framing members

APPLICATIONS

- 4" square single device rings are used with 4" square boxes to mount switches, receptacles and devices

STANDARD MATERIAL

- Galvanized steel or 316 stainless steel

CERTIFICATIONS

- UL, cULus Listed



52C14-5/8



52C2-5/8



52C16



52C26

PART #	DESCRIPTION	RAISED	CUBIC INCHES (CM³)	MASTER QTY.
52C62A	FOR DRYWALL	FLAT	---	50
52C62	FOR DRYWALL	1/4"	1.5 (24.6)	50
52C13	FOR DRYWALL	1/2"	3.5 (57.3)	50
52C14-5/8	FOR DRYWALL	5/8"	4.5 (73.7)	50
52C2-5/8*	"SKINNY DEVICE" FOR DRYWALL/TILE	5/8"	4.5 (73.7)	50
52C14	FOR DRYWALL	3/4"	5.5 (90.1)	50
52C15	FOR DRYWALL	1"	7.5 (122.9)	25
52C16	FOR DRYWALL	1-1/4"	8.5 (139.3)	25
52C22	FOR DRYWALL	1-1/2"	11.3 (185.2)	25
52C23	FOR DRYWALL	2"	14.5 (237.6)	25
52C26	FOR DRYWALL OR TILE **	2-1/2"	16.0 (262.1)	25
52C28	FOR DRYWALL OR TILE **	3-1/2"	22.5 (368.7)	25
52C62A-SS	FOR DRYWALL FINISH , 316 STAINLESS STEEL	FLAT	---	50
52C62-SS		1/4"	1.5 (24.6)	50
52C13-SS		1/2"	3.5 (57.3)	50
52C14-SS		3/4"	4.5 (73.7)	50
52C15-SS		1"	7.5 (122.9)	25
52C16-SS		1-1/4"	7.5 (122.9)	25
52C22-SS		1-1/2"	11.3 (185.2)	25
52C23-SS		2"	14.5 (237.6)	25

*Not UL Listed

**From UL Listed components