nVent CADDY Pyramid ST Fixed Strut Support - PSF6C












- Provides superior support for pipe, conduit, duct, cable tray and equipment
- Foam bottom offers low abrasion interface for better roof membrane protection
- Compatible with roof surfaces including single ply, bituminous, metal and spray foam
- Provides superior load distribution, even with varying rooftop surfaces
- Ready to use out of the box, saving installation time and labor
- Multiple sizes and load ratings offer the ability to tailor the solution to the application
- Easy to transport to the roof
- Hot-dip galvanized and UV stabilized for long lasting performance
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credits





D IN I	DCE/0
Part Number	PSF6C
Material	Polyethylene Polypropylene Steel
Finish	Hot-Dip Galvanized
Temperature	-50 to 150 °F
Static Load Safety Factor	3:1
Length 1 (L1)	6"
Length 2 (L2)	8"
Height (H)	4.8"
Width (W)	6"
Surface Area	41 in ²
Unit Weight	1 lb
Static Load (F)	300 lb
Standard Packaging Quantity	20 pc
UPC	78285684299
EAN-13	8711893138832

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.



