

20-141M, 20-143M
& AMT-145M



FIG-1

FIG-2

DISCONNECTS - FULLY INSULATED

- Rated at 600 Volt Max.
- Temperature rating: 167°F (75°C).



Part #	Color	Pack Qty.	Length (L)		Width (W)		Barrel I.D. (C)		Wire Range	Tab Size	Type
			Inches	MM	Inches	MM	Inches	MM			
15-152P	Red/Blue	6 Pairs/Clam	0.87 - .95	22 - 24	.25 - .26	6.4 - 6.6	.067 - .091	1.7 - 2.3	#22 - #14 AWG	.250"	F/M Pairs
20-151P	Red	10 Pairs/Clam	0.87 - .95	22 - 24	.25 - .26	6.4 - 6.6	0.067	1.7	#22 - #16 AWG	.250"	F/M Pairs
15-151F	Red	15/Clam	0.87	22	0.26	6.6	0.067	1.7	#22 - #16 AWG	.250"	Female
15-151M	Red	15/Clam	0.95	24	0.25	6.4	0.067	1.7	#22 - #16 AWG	.250"	Male
10-151F	Red	100/Clam	0.87	22	0.26	6.6	0.067	1.7	#22 - #16 AWG	.250"	Female
15-153F	Blue	15/Clam	0.87	22	0.26	6.6	0.091	2.3	#16 - #14 AWG	.250"	Female
15-153M	Blue	15/Clam	0.95	24	0.25	6.4	0.091	2.3	#16 - #14 AWG	.250"	Male
20-153F	Blue	20/Clam	0.87	22	0.26	6.6	0.091	2.3	#16 - #14 AWG	.250"	Female
20-153P	Blue	10 Pairs/Clam	0.87 - .95	22 - 24	.25 - .26	6.35 - 6.6	0.091	2.3	#16 - #14 AWG	.250"	F/M Pairs
10-153P	Blue	50 Pairs/Clam	0.87 - .95	22 - 24	.25 - .26	6.35 - 6.6	0.091	2.3	#16 - #14 AWG	.250"	F/M Pairs
10-153M	Blue	80/Clam	0.95	24	0.25	6.4	0.091	2.3	#16 - #14 AWG	.250"	Male
10-153F	Blue	100/Clam	0.87	22	0.26	6.6	0.091	2.3	#16 - #14 AWG	.250"	Female
21-155F	Yellow	4/Clam	0.95	24	0.26	6.6	0.134	3.4	#12 - #10 AWG	.250"	Female
21-155M	Yellow	4/Clam	0.98	25	0.25	6.4	0.134	3.4	#12 - #10 AWG	.250"	Male
15-155F	Yellow	10/Clam	0.95	24	0.26	6.6	0.134	3.4	#12 - #10 AWG	.250"	Female
15-155M	Yellow	10/Clam	0.98	25	0.25	6.4	0.134	3.4	#12 - #10 AWG	.250"	Male
10-155F	Yellow	50/Clam	0.95	24	0.26	6.6	0.134	3.4	#12 - #10 AWG	.250"	Female




20-161P, 20-1636
& 15-162P

BULLET SPLICES - FULLY INSULATED


- Rated at 600 Volt Max.
- Temperature rating: 167°F (75°C).



Part #	Color	Pack Qty.	Length (L)		Width (W)		Barrel I.D. (C)		Wire Range	Tab Size	Type
			Inches	MM	Inches	MM	Inches	MM			
20-161P	Red	5 Pairs/Clam	.87 - .99	22 - 25.2	.15 - .16	3.9 - 4	0.067	1.7	#22 - #16AWG	.156"	F/M Pairs
21-161F	Red	6/Clam	0.99	25.2	0.15	3.9	0.067	1.7	#22 - #16AWG	.156"	Female
21-161M	Red	6/Clam	0.87	22	0.16	4	0.067	1.7	#22 - #16AWG	.156"	Male
15-163P	Blue	5 Pairs/Clam	.87 - .99	22 - 25.2	.15 - .16	3.9 - 4	0.091	2.3	#16 - #14 AWG	.156"	F/M Pairs
20-163F	Blue	20/Clam	0.99	25.2	0.15	3.9	0.091	2.3	#16 - #14 AWG	.156"	Female
20-163M	Blue	20/Clam	0.87	22	0.16	4	0.091	2.3	#16 - #14 AWG	.156"	Male
10-163P	Blue	50 Pairs/Clam	.87 - .99	22 - 25.2	.15 - .16	3.9 - 4	0.091	2.3	#16 - #14 AWG	.156"	F/M Pairs
20-163P	Blue	10 Pairs/Clam	.87 - .99	22 - 25.2	.15 - .16	3.9 - 4	0.091	2.3	#16 - #14 AWG	.156"	F/M Pairs
15-162P	Yellow	5 Pairs/Clam	.93 - 0.95	23.5 - 24	0.19 - 2	4.9 - 5	0.134	3.4	#12 - #10 AWG	.156"	F/M Pairs



20-2218



20-100



20-1210

TAP SPLICES

- Secure connections without stripping wire.
- Rated at 600 Volt Max.
- Temperature rating: 221°F (105°C).

Part #	Color	Pack Qty.	Wire Range
20-2218	Red	5/clam	#22 - #18 AWG
20-100	Blue	5/Clam	#16 - #14 AWG
21-100	Blue	5/Clam	#16 - #14 AWG
10-100	Blue	25/Clam	#16 - #14 AWG
20-1210	Yellow	3/Clam	#12 - #10 AWG