


GB Xtreme® TERMINALS

Constructed with Heat Shrink insulation - adhesive lined to waterproof and environmentally seal electrical connections when crimped and heated.

- Insulates and protects connections from wire pullout, moisture intrusion and abrasion.
- Heat-activated adhesive melts and flows to create a seal.
- Resists salt water, oil, gasoline and other environmental contaminants.
- Rated at 600 Volt Max.
- Temperature rating: -67° to 221°F (-55° to 105°C).
- 2.5:1 shrink ratio.
- Heat to 275°F (135°C).




AMT-120, AMT-123 & AMT-126

BUTT SPLICES

Part #	Color	Pack Qty.	Length (L)		Barrel I.D. (C)		Wire Range
			Inches	MM	Inches	MM	
AMT-120	Red	3/Clam	1.33	33.71	0.07	1.7	#22 - #18 AWG
AMT-4120	Red	8/Clam	1.33	33.71	0.07	1.7	#22 - #18 AWG
AMT-121	Red	25/Clam	1.33	33.71	0.07	1.7	#22 - #18 AWG
AMT-123	Blue	3/Clam	1.33	33.71	0.09	2.3	#16 - #14 AWG
AMT-4123	Blue	7/Clam	1.33	33.71	0.09	2.3	#16 - #14 AWG
AMT-124	Blue	25/Clam	1.33	33.71	0.09	2.3	#16 - #14 AWG
AMT-126	Yellow	3/Clam	1.33	33.71	0.13	3.4	#12 - #10 AWG
AMT-5126	Yellow	4/Clam	1.33	33.71	0.13	3.4	#12 - #10 AWG
AMT-4126	Yellow	5/Clam	1.33	33.71	0.13	3.4	#12 - #10 AWG
AMT-127	Yellow	25/Clam	1.33	33.71	0.13	3.4	#12 - #10 AWG
AMT-5121*	Red	5/Clam	1.61	40.89	0.07	1.7	#22 - #18 AWG
XTM-240*	Red	6/Clam	1.61	40.89	0.07	1.7	#22 - #18 AWG
AMT-5123*	Blue	5/Clam	1.61	40.89	0.09	2.3	#16 - #14 AWG
XTM-245*	Blue	6/Clam	1.61	40.89	0.09	2.3	#16 - #14 AWG
XTM-250*	Yellow	4/Clam	1.61	40.89	0.13	3.4	#12 - #10 AWG
GBX-TK*	Red/Blue/Yellow	24/Clam	1.61	40.89	.07 - .13	1.7 - 3.4	#22 - #10 AWG

*Solder Ring Terminals




AMT-100, AMT-103 & AMT-108

RING TERMINALS

Part #	Color	Pack Qty.	Length (L)		Width (W)		Barrel I.D. (C)		Wire Range	Stud Size
			Inches	MM	Inches	MM	Inches	MM		
AMT-100	Red	3/Clam	1.37	34.80	0.4	10.16	0.067	1.7	#22 - #18 AWG	10
AMT-4100	Red	6/Clam	1.37	34.80	0.4	10.16	0.067	1.7	#22 - #18 AWG	10
AMT-103	Blue	3/Clam	1.37	34.80	0.4	10.16	0.091	2.3	#16 - #14 AWG	8
AMT-4103	Blue	6/Clam	1.37	34.80	0.4	10.16	0.091	2.3	#16 - #14 AWG	8
AMT-106	Yellow	3/Clam	1.37	34.80	0.4	10.16	0.131	3.4	#12 - #10 AWG	8
AMT-108	Yellow	3/Clam	1.88	47.75	0.56	14.22	0.131	3.4	#12 - #10 AWG	1/4"
AMT-4106	Yellow	5/Clam	1.37	34.80	0.4	10.16	0.131	3.4	#12 - #10 AWG	10
AMT-5104*	Blue	4/Clam	1.67	42.42	0.4	10.16	0.091	2.3	#16 - #14 AWG	10
AMT-5106*	Yellow	3/Clam	1.67	42.42	0.4	10.16	0.131	3.4	#12 - #10 AWG	10


*Solder Ring Terminals



AMT-110, AMT-113 & AMT-116

SPADE TERMINALS

Part #	Color	Pack Qty.	Length (L)		Width (W)		Barrel I.D. (C)		Wire Range	Stud Size
			Inches	MM	Inches	MM	Inches	MM		
AMT-110	Red	3/Clam	1.38	35.05	0.36	9.14	0.067	1.7	#22 - #18 AWG	8 to 10
AMT-4110	Red	6/Clam	1.38	35.05	0.36	9.14	0.067	1.7	#22 - #18 AWG	8 to 10
AMT-113	Blue	3/Clam	1.38	35.05	0.36	9.14	0.091	2.3	#16 - #14 AWG	8 to 10
AMT-4113	Blue	6/Clam	1.38	35.05	0.36	9.14	0.091	2.3	#16 - #14 AWG	8 to 10
AMT-116	Yellow	3/Clam	1.39	35.05	0.4	10.16	0.131	3.4	#12 - #10 AWG	8 to 10
AMT-4116	Yellow	5/Clam	1.39	35.05	0.4	10.16	0.131	3.4	#12 - #10 AWG	8 to 10



XTM-220, XTM-225

DISCONNECT- SOLDER

Part #	Color	Pack Qty.	Length (L)		Width (W)		Barrel I.D. (C)		Wire Range	Tab Size	Type
			Inches	MM	Inches	MM	Inches	MM			
XTM-220	Red	3 Pairs/Clam	1.47 - 1.55	37.34 - 39.37	0.23	5.842	0.067	1.7	#22 - #18 AWG	.250"	F/M Pairs
XTM-225	Blue	3 Pairs/Clam	1.47 - 1.55	37.34 - 39.37	0.26	6.604	0.091	2.3	#16 - #14 AWG	.250"	F/M Pairs

