



HWT-0722

HEAVY-WALL HEAT SHRINK TUBING

Provides maximum reliability for insulating and protecting wire, cables and terminations.

- High impact, abrasion and corrosion resistance.
- Submersible and great for direct burial installations.
- Inner adhesive bonds to plastics, rubber, neoprene, steel, polyethylene.
- Continuous operating temperature: -55 °C (-67 °F) - 125 °C (257 °F).

Part #	Pack Qty.	Inside Dia.		Length
		Before	Finished	
HWT-0722	1/bag	3/4"	7/32"	6"
HWT-1138	1/bag	1 3/32"	3/8"	6"
HWT-1550	1/bag	1 1/2"	1/2"	6"
HWT-0033	3	1/2"	1/8"	6"
HWT-0020	2/bag	5/8"	3/16"	6"
HWT-0025	1/bag	7/8"	1/4"	6"



BHST-200

NEW BUTANE MINI-TORCH

Used to heat shrink tubes and terminals.

- Contains butane refill, precision soldering attachment & safety standing base.
- Includes child safety lock, air adjustment ring, flame control adjuster, continuous flame lock & built-in fuel cell/refilling valve

Part #	Pack Qty.	Operating Temp	Refill Size
BHST-200	1/clam	1875°F (1000°C)	2.5 oz/can



SB1-25

WIRE MANAGEMENT ACCESSORIES

NEW SNAP-IN METAL STUD BUSHING

Universal Stud Insulators provide 360° protection for cable runs through metal studs, where sharp hole edges could otherwise gouge plastic or rubber-jacketed electric, communications or network cable.



- Easy twist apart and snap together
- Constructed from durable polypropylene
- Helps protect and insulate wires and cables from metal studs
- Design accommodates any shape pre-punched hole or standard field-punched holes.

Part #	Size	Pack Qty.	Color
SB1-25	Applied product, Inside Diameter: 1-1/8"	25/bag	Red
SB1-50	Outer Diameter: 1-3/8"	50/bag	Red
SB1-100	Bushing Diameter: 2-1/4"	100/bag	Red



GROMMETS

Offers protection from to wires in passing through drilled holes.

- Prevents sharp edges from cutting or fraying wire.
- Made from rubberized material.



GHG-1550

Part #	Pack Qty.	Color	Size
GHG-1525	6/Cd	Black	1/4"
GHG-1538	5/Cd	Black	3/8"
GHG-1550	4/Cd	Black	1/2"
GHG-1575	3/Cd	Black	3/4"
GHG-AST	8/Clam	Black	1/4" - 3/4"