HEAT SHRINK & BUTANE TORCH

THIN-WALL HEAT SHRINK

Great for cable insulation, marking and bundling, with superior mechanical, abrasion and moisture protection.

- Flame retardant, meets UL 224 VW-1.
- Resists common fluids and solvents. Material is Polyolefin.
- Meets UL 224, 125˚C; CSA C22.2 No. 198.1, 125˚C; MIL-DTL-23053/5, Class 1 & 2, AMS 3636 &3637; DEF Stan 59-79, Issue 3 Type 2a.
- Continuous operating temperature: -40˚C (40˚F) - 125˚C (257˚F).
- Shrink temperature: 125˚C (257˚F) - 250˚C (480˚F).
- 600 V/Mil Dielectric strength. 2:1 shrink ratio.

Part #	Pkg Qty	Before	Finished	Length	Conductor Gauge AWG*																Color
					24	22	20	18	16	14	12	10	8	6	4	2	1	1/0	2/0	3/0	4/0	
HST-093	8 pcs	3/32"	3/64"	4"	•																	Black
HST-093B	8 pcs	3/32"	3/64"	3"	•																	Black
HST-093W	8 pcs	3/32"	3/64"	3"	•																	White
HST-100	1 pc	3/16"	3/32"	8'		•	•	•	•	•	•											Red
HST-100B	1 pc	3/16"	3/32"	8"		•	•	•	•	•	•											Black
HST-101	1 pc	1/4"	1/8"	8'				•	•	•	•	•										Blue
HST-101B	1 pc	1/4"	1/8"	8'				•	•	•	•	•										Black
HST-102	1 pc	5/16"	5/32"	8"						•	•	•	•	•								Yellow
HST-102B	1 pc	5/16"	5/32"	8"						•	•	•	•	•								Black
HST-125	7 pcs	1/8"	1/16"	4"		•	•	•														Black
HST-125B	8 pcs	1/8"	1/16"	3"		•	•	•														Black
HST-125W	8 pcs	1/8"	1/16"	3"		•	•	•														White
HST-187B	5 pcs	3/16"	3/32"	3"		•	•	•	•	•	•											Black
HST-187R	5 pcs	3/16"	3/32"	3"		•	•	•	•	•	•											Red
HST-187	8 pcs	3/16"	3/32"	4"			•	•	•	•	•											Black
HST-187W	5 pcs	3/16"	3/32"	3"			•	•	•	•	•											White
HST-250	6 pcs	1/4"	1/8"	4"				•	•	•	•	•										Black
HST-250B	5 pcs	1/4"	1/8"	3"				•	•	•	•	•										Black
HST-250R	5 pcs	1/4"	1/8"	3"				•	•	•	•	•										Red
HST-250W	5 pcs	1/4"	1/8"	3"				•	•	•	•	•										White
HST-375	3 pcs	3/8"	3/16"	4"						•	•	•	•	•								Black
HST-375B	3 pcs	3/8"	3/16"	3"						•	•	•	•	•								Black
HST-375R	3 pcs	3/8"	3/16"	3"						•	•	•	•	•								Red
HST-375W	3 pcs	3/8"	3/16"	3"						•	•	•	•	•								White
HST-500	3 pcs	1/2"	1/4"	4"								•	•	•	•	•						Black
HST-500B	3 pcs	1/2"	1/4"	3"								•	•	•	•	•						Black
HST-500R	3 pcs	1/2"	1/4"	3"								•	•	•	•	•						Red
HST-500W	3 pcs	1/2"	1/4"	3"								•	•	•	•	•						White
HST-750	2 pcs	3/4"	3/8"	4"											•	•	•	•	•	•		Black
HST-750B	2 pcs	3/4"	3/8"	3"											•	•	•	•	•	•		Black
HST-999	2 pcs	1"	1/2"	4"															•	•	•	Black
HST-ASTB	160 pcs	3/32", 1/8", 3/16", 1/4", 3/4", 1/16", 3/8"	3/64", 1/16", 3/32", 1/8", 3/8", 1/32", 3/16"	3"	•	•	•	•	•	•	•	•	•	•	•	•						Black
HST-ASTBR	4 pcs	1"	3/8"	3"															•	•	•	Black & Red
XTM-301	8 pcs	3/16", 3/4"	3/32", 3/8"	3"		•	•	•	•	•	•				•	•	•	•	•	•		Black
HST-AST	8 pcs	1/8",3/16", 1/4"	1/16", 3/32", 1/8"	4"	•	•	•	•	•	•	•	•	•	•	•	•						Black
HST-107	7 pcs	1/8", 1/4", 3/8", 1/2"	1/16", 1/8", 3/16", 1/4"	3"		•	•	•	•	•	•	•	•	•	•	•						Assorted (Red, Blue, Yellow)
HST-ASTA	160 pcs	3/32", 1/8", 3/16", 1/4", 3/4", 1/16", 3/8"	3/64", 1/16", 3/32", 1/8", 3/8", 1/32", 3/16"	3"	•	•	•	•	•	•	•	•	•	•	•	•						Assorted (Red, Blue, Yellow)
XTM-305	5 pcs	3/8"	3/16"	3"						•	•	•	•	•								Assorted (Red, Blue, Yellow)

**Sizes shown are approximate and may vary according to manufacturer and insulation system for each wire.*