



Twin Screw All-Purpose Connectors

For Flex • AC • MCI • NM cable. Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	CABLE RANGE	END STOP DIAMETER
4200	04200	1/4	1/4	25	25	1.200	.900	.225 - .610	.380



See chart on page E-27 for list of cable types.
Concrete tight when taped.



THE 4200...


- Allows you to securely hold cables in low profile height fixtures with 1/4" knockouts.
- Fits both standard round 1/4" KO (17/32" diameter) and 5/8" diameter KO with flats.
- Is furnished with 1/4-18 n.p.s. fixture nut for easy tightening.
- Is recommended for use with non-metallic sheathed cable, AC, flexible metal conduit, MC cable both steel and aluminum jacketed.
- Is primarily for use with low silhouette under-cabinet fluorescent fixtures.
- Normally only one fitting is supplied with lighting fixtures. Additional connectors are needed when multiple fixtures are wired in-line.



Twin Screw All-Purpose Connectors

For Flex • AC • MCI • NM cable. Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
4201	04201	1/2	1/2	25	250	1.535	1.139	.610	.630-.810	.615
4202	04202	3/4	3/4	20	200	1.528	1.276	.814	.830-1.090	.820
4203	04203	1	1	10	50	1.726	1.605	.985	1.00-1.365	.985
4204	04204	1-1/4	1-1/4	5	25	1.783	1.885	1.375	1.385-1.640	1.365



Add suffix "A" to catalog number for insulated throat.
See chart on page E-27 for list of cable types.
Concrete tight when taped.



Cable Types and Ranges

Style	Part Number (ST = Snap-Tite®)	Knock-Out Size	AC90	AC90	TECK90	Outer Armor Diameter Flex • A/C • M/C	Throat Diameter	Number of Cables	Insulated Throat	Flexible Metal Conduit (FMC)				Armored Cable (A/C)		Metal Clad Cable (M/C)		A/C M/C
										Steel	Aluminum	Reduced Wall Steel	Reduced Wall Aluminum	Steel	Aluminum	Steel	Aluminum Corrugated	
Single Screw Clamp Type	L16ST	1/2	0.440 - 0.650	0.440 - 0.650		0.290 - 0.670	0.400 x 0.580	1		•	•	•	•	•	•	•	•	•
	L160	1/2	0.446 - 0.650			0.370 - 0.510	0.312	1		•	•	•	•	•	•	•	•	•
	L160ST	1/2	0.446 - 0.650			0.370 - 0.510	0.312	1		•	•	•	•	•	•	•	•	•
	L17	1/2	0.630 - 0.890	0.630 - 0.890	0.650 - 0.850	0.630 - 0.890	0.620	1		•	•	•	•	•	•	•	•	•
Single Screw Clamp Type (cont.)	L17ST	1/2	0.630 - 0.890	0.630 - 0.890	0.650 - 0.850	0.630 - 0.890	0.620	1		•	•	•	•	•	•	•	•	•
	L18	3/4	0.630 - 0.890	0.820 - 1.040	0.890 - 0.990	0.820 - 1.040	0.818	1		•	•	•	•	•	•	•	•	•
	L18ST	3/4	0.630 - 0.890	0.820 - 1.040	0.890 - 0.990	0.820 - 1.040	0.818	1		•	•	•	•	•	•	•	•	•
	L19	1	0.630 - 0.890	0.630 - 0.890		1.040 - 1.400	1.030	1		•	•	•	•	•	•	•	•	•
	L19ST	1	0.630 - 0.890	0.630 - 0.890		1.040 - 1.400	1.030	1		•	•	•	•	•	•	•	•	•
	SG38	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.395	1		•	•	•	•	•	•	•	•	•
	SG38A	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.400	1	•	•	•	•	•	•	•	•	•	•
Straight SADDLE GRIP® Connectors	SG38AST	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.400	1	•	•	•	•	•	•	•	•	•	•
	SG380	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.400 x 0.580	1		•	•	•	•	•	•	•	•	•
	SG380A	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.340 x 0.510	1	•	•	•	•	•	•	•	•	•	•
	SG380AST	1/2	0.450 - 0.560	0.450 - 0.560		0.430 - 0.630	0.340 x 0.510	1	•	•	•	•	•	•	•	•	•	•
	SG40	1/2				0.630 - 0.790	0.630	1		•	•	•	•	•	•	•	•	•
	SG50	1/2		0.850		0.630 - 0.900	0.630	1		•	•	•	•	•	•	•	•	•
	SG50A	1/2		0.850		0.630 - 0.900	0.560	1	•	•	•	•	•	•	•	•	•	•
	SG50ST	1/2		0.850		0.630 - 0.900	0.630	1		•	•	•	•	•	•	•	•	•
	SG50AST	1/2		0.850		0.630 - 0.900	0.560	1	•	•	•	•	•	•	•	•	•	•
	SG75	3/4		0.850 - 1.050		0.840 - 1.110	0.835	1		•	•	•	•	•	•	•	•	•
	SG75A	3/4		0.850 - 1.050		0.840 - 1.110	0.835	1	•	•	•	•	•	•	•	•	•	•
	SG75ST	3/4		0.850 - 1.050		0.840 - 1.110	0.835	1		•	•	•	•	•	•	•	•	•
	SG75AST	3/4		0.850 - 1.050		0.840 - 1.110	0.765	1	•	•	•	•	•	•	•	•	•	•
Duplex SADDLE GRIP® Connectors	SG3838	1/2		0.450 - 0.550		0.430 - 0.605		2		•	•	•	•	•	•	•	•	•
	SG3838A	1/2		0.450 - 0.550		0.430 - 0.605		2	•	•	•	•	•	•	•	•	•	•
	SG3838ST	1/2		0.450 - 0.550		0.430 - 0.605		2		•	•	•	•	•	•	•	•	•
	SG3838AST	1/2		0.450 - 0.550		0.430 - 0.605		2	•	•	•	•	•	•	•	•	•	•
Two Screw Clamp Type Connectors	4200	1/4				0.410 - 0.605	0.380	1		•	•	•	•	•	•	•	•	•
	4201	1/2				0.600 - 0.825	0.615	1		•	•	•	•	•	•	•	•	•
	4202	3/4				0.830 - 1.090	0.820	1		•	•	•	•	•	•	•	•	•
	4203	1				1.000 - 1.370	0.985	1		•	•	•	•	•	•	•	•	•
	4204	1-1/4				1.250 - 1.640	1.365	1		•	•	•	•	•	•	•	•	•
	4501	1/2				0.410 - 0.590	0.620	1		•	•	•	•	•	•	•	•	•
	4501ST	1/2				0.410 - 0.590	0.620	1		•	•	•	•	•	•	•	•	•
	4502	1/2				0.620 - 0.870	0.635	1		•	•	•	•	•	•	•	•	•
	4502ST	1/2				0.620 - 0.870	0.635	1		•	•	•	•	•	•	•	•	•
	840	1/2				0.370 - 0.590	0.400 x 0.580	1		•	•	•	•	•	•	•	•	•
	840ST	1/2				0.370 - 0.590	0.400 x 0.580	1		•	•	•	•	•	•	•	•	•
	8400	1/2				0.370 - 0.590	0.400	1		•	•	•	•	•	•	•	•	•
	8400ST	1/2				0.370 - 0.590	0.375	1		•	•	•	•	•	•	•	•	•
	8401	1/2				0.410 - 0.590	0.375	1		•	•	•	•	•	•	•	•	•
	8402	3/4				0.525 - 0.780	0.620	1		•	•	•	•	•	•	•	•	•
	8403	1		1.000		0.780 - 1.000	0.840	1								•	•	•
	8404	1-1/4		1.020 - 1.240		1.020 - 1.345	1.030	1								•	•	•
	8405	1-1/2		1.400 - 1.750		1.400 - 1.750	1.390	1								•	•	•
	8407	2		1.640 - 2.300		1.640 - 2.300	1.610	1								•	•	•
	8408	2-1/2				1.950 - 2.360	1.924	1								•	•	•
	8409	3				2.300 - 3.070	2.390	1								•	•	•
	8410	3-1/2				2.860 - 3.600	2.830	1								•	•	•