

90° Non-Metallic Connectors



For use with non-metallic liquid tight conduit, type B only. 90° connector provides a smooth gradual radius bend. Wiring is easily pulled or pushed through fitting and there are no sharp edges that could strip wire. Produced from UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT9038	54903	3/8	1/2	10	50	2.305	.562	2.460
NMLT9050	54905	1/2	1/2	10	50	2.242	.562	2.460
NMLT9075	54907	3/4	3/4	10	50	2.550	.545	2.840
NMLT90100	54901	1	1	5	25	3.150	.630	3.680
NMLT90125	54912	1-1/4	1-1/4	5	25	3.420	.645	4.650
NMLT90150	54915	1-1/2	1-1/2	2	10	4.510	.660	4.470
NMLT90200	54920	2	2	2	10	4.850	.670	5.290



MADE IN USA.

Add suffix "BL" to Catalog # when ordering in black, for example NMLT9050BL.



LIQUID TIGHT

Straight Non-Metallic Connectors



For use with non-metallic liquid tight conduit, type B only. Produced from UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT38	54380	3/8	1/2	25	100	1.545	.535	1.410
NMLT50	54500	1/2	1/2	25	100	1.545	.535	1.410
NMLT75	54750	3/4	3/4	10	50	1.600	.550	1.595
NMLT100	54100	1	1	5	25	1.975	.670	1.930
NMLT125	04223	1-1/4	1-1/4	5	25	2.293	.645	2.428
NMLT150	04222	1-1/2	1-1/2	2	10	2.175	.660	2.700
NMLT200	04221	2	2	2	10	2.400	.670	3.360



MADE IN USA.

Add suffix "BL" to Catalog # when ordering in black, for example NMLT38BL.



INSTALLATION INSTRUCTIONS

Arlington's reusable Liquid tight Fittings may be secured to conduit while fully assembled because of our no spin ferrule. Simply loosen nut, and screw onto conduit. A positive liquid tight seal is provided by our pressure sensitive internal gland when the nut is tightened. A liquid tight seal is also assured between the fitting and box by a sealing ring.