

NONMETALLIC CABLE TIES										REV	DATE	DESCRIPTION				ECO	BY	C'H'K.
										B	01/09/2014	ADD NOTE 4 WITH FLAG PER M/U.				34552	RB	AM
BURNDY ITEM NUMBER	BURNDY CATALOG NUMBER	CABLE TIE CONFIG	UL TYPE DESIGNATION	TENSILE STRENGTH lb / [N]	MATERIAL	COLOR	BUNDLE DIA MIN IN / [MM]	BUNDLE DIA MAX IN / [MM]	LENGTH IN / [MM]	WIDTH IN / [MM]	MIN INSTALL TEMP F / C	MIN OPER TEMP F / C	MAX OPER TEMP F / C	PACKAGE QTY	BAG LENGTH +/- .25	BAG WIDTH +/- .25		
10023292	CT18075C	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	8	4		
10023303	CT18075M	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	10	7		
10023304	CT18125C	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	10	4		
10023307	CT18125C3	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	ORANGE	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	10	4		
10023308	CT18125C4	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	YELLOW	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	10	4		
10023315	CT18125M	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	12	9		
10023316	CT18200C	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023317	CT18200C1	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	BROWN	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023318	CT18200C2	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	RED	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023321	CT18200C5	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	GREEN	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023322	CT18200C6	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	BLUE	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023327	CT18200M	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	2.00 / [51]	8.1 / [206]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	12	8		
4 10023328	CT18075C00	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV Black ²	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	8	4		
4 10023329	CT18075M00	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV Black ²	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	10	7		
4 10023334	CT18075C0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	8	4		
4 10023335	CT18075M0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	10	7		
10023336	CT18125C0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	10	4		
10023337	CT18125M0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	1.25 / [32]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	10	4		
10023338	CT18200C0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	2.00 / [51]	6.1 / [155]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	13	5		
10023339	CT18200M0	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6	UV BLACK	.06 / [1.6]	2.00 / [51]	8.1 / [206]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	1000	12	8		
4 10023669	CT18075MH4C	FIG. 2	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	.75 / [19]	4.25 / [108]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	6	4		
4 10023670	CT18075MH4M	FIG. 2	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	.75 / [19]	4.25 / 108]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	6	4		
4 10023689	CT18075IDC	FIG. 3	TYPE 2/21	18 / [80]	NYLON 6/6	NATURAL	.06 / [1.6]	.75 / [19]	4.0 / [102]	0.1 / [2.5]	32 / 0	-40 / -40	185 / 85	100	6	4		
4 50027390	CTHS18075M	FIG. 1	TYPE 2/21	18 / [80]	NYLON 6/6 HEAT STABILIZED	HS UV BLK	.06 / [1.6]	.75 / [19]	4.1 / [104]	0.1 / [2.5]	18 / -8	-40 / -40	221 / [105]	100	10	7		

FIG. 1

FIG. 2

FIG. 3

NOTES:

- DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS ROUNDED OFF TO THE NEAREST MILLIMETER, UNLESS OTHERWISE SPECIFIED AND ARE FOR REFERENCE ONLY.
- COLOR "UV BLACK MATERIAL IS NYLON 6/6 UV STABILIZED. COLOR "UV BLACK² MATERIAL IS 2% CARBON UV STABILIZED.
- OPTIMUM STORAGE CONDITIONS FOR NYLON 6/6 CABLE TIES IS 70°F / 21°C AT 50% RELATIVE HUMIDITY. CABLE TIES SHOULD BE STORED IN THE MANUFACTURE'S ORIGINAL PACKAGING UNTIL READY FOR USE.

4 THESE ITEMS MIL SPEC MS3367.

TO ORDER BURNDY PRODUCTS CALL

UNITED STATES
1-800-346-4175 (LONDONDERRY, NH)

CANADA:
1-800-361-6975 (QUEBEC)
1-800-387-6487 (ALL OTHER PROVINCES)

FOR PRODUCT INFO: <http://www.burndy.com>

UNIRAP™

ITEM NO: SEE TABLE

CAT. NO: SEE TABLE

DRAWN BY: A MONTMINY	9/19/2013
CHECKER:	
DSN APRVL: A MONTMINY	1/6/2014
MFG APRVL: P. KEENAN	12/26/2013
QA APRVL: C. KOWALCZYK	1/6/2014
MKT APRVL: R. CAVANAUGH	1/6/2014

PROD FAM:		DRAWING NO	REV
PROJECT #:	SIZE	50034342	B
DOCUMENT TYPE: SALES	B	SHEET 1 OF 1	
REL LEVEL: Released			