

YDS25AT, Aluminum Full Tension **Sleeve Splice**

By Burndy Catalog # YDS25AT

Aluminium Hysplice, 7-1/4 in L, Full Tension Sleeve for All Aluminum Compressed and Compact Conductors, Die index:243.



Application

For All Aluminum Compressed And Compact Conductors

General

YDS25AT Catalog Number Color Code Yellow Splice Connector Type BG or 243 Die Index Yes **EU RoHS Indicator** Insulation Material Aluminum

Plated Plating Type Unplated

Prefilled Oxide Inhibitor

Sub Brand **HYSPLICE** HYSPLICE™ Trade Name Type YDS-AT UPC 781810820971 UPC 12 Digit 7818108209711

Dimensions

Dimension - B Length fraction 3-53/93 in Dimension - B Length inch 3.57 in Dimension - L Length Overall 185 mm

mm

Dimension - Length Overall 7.27 in

Dimension - Outside Diameter 0.62 in

inch

Conductor Related

Conductor - ACSR Cmpt Size 1/0 AWG Conductor - ACSR Cmpt Size 1/0 AWG Range

1/0 AWG Conductor - AL Str Size Conductor - AL Str Size 1/0 AWG

Range

 ACSR C Str-Size Conductor Type

• AL C Str-Size

Certifications And Compliance

Certification - CSA Approved Certification - ETL No Certification - UL Recognized Nο Certification - cULus Standards - RoHS Compliance CM Status **UL** Listed

Logistics

Carton Quantity 25 Minimum Pack Quantity Pallet Quantity 9800

Product Assets

Catalogs - Full Line BURNDY Catalog Catalogs - Section H - Overhead Distribution Customer Notices - Prop 65 Notice Product Cross Section Image(s) - BUR YDS-AT LineArt Sales Drawings - SD..021880-01

No

