

EDGE™ Housing 2 rack unit, Gray, holds up to 24 EDGE modules or panels

CORNING

**Part Number:
EDGE-02U**

EDGE™ housings are high-density, preterminated fiber optic hardware solutions. They offer industry-leading connector density and easy finger/toolless access to enable faster moves, adds, and changes (MACs). The units can be configured to accommodate 96, 144, 288, or 576 fibers.

EDGE housings can be rack- or cabinet-mounted and are ideal for data centers, local area network (LAN) and storage area network (SAN) applications, as well as enterprise networks.



EDGE™ Housing 2 rack unit, Gray, holds up to 24 EDGE modules or panels



EDGE™ Housing, 2 rack unit, holds up to 24 EDGE modules or panels



EDGE™ Housing, 2 rack unit, holds up to 24 EDGE modules or panels

Specifications

General Specifications	
Product Type	Fiber Optic Hardware
Access Type	Front and rear access slidable
Lockable	Yes, rear side
Mounting Type	Rack Mount, Cabinet-mount
Application	Data Center, Data Center LAN/SAN, Enterprise Networks

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Number of Modules	24
Cable entry type	Side brush entry
Number of Panels/Cassettes per Housing	24

EDGE™ Housing 2 rack unit, Gray, holds up to 24 EDGE modules or panels

CORNING

Design

Cable Entry Direction	Rear
Housing Type	EDGE™
Color	Silver
Panel or Cassette Type	EDGE™
Panel or Module Type	EDGE™
Fiber Capacity	288

Design - Adapter

Housing Color	Silver
---------------	--------

Dimensions

Height	88 mm (3.46 in)
Width	432 mm (17.01 in)
Depth	561 mm (22.09 in)

Shipping Dimensions

Height	216 mm (8.5 in)
Width	565 mm (22.24 in)
Depth	660 mm (25.98 in)

Ordering Information

Product Number	EDGE-02U
EAN Code	4056418144498
Weight	8.6 kg
Package Contents	"EDGE™ Housing 2U; Quick Start Guide, #12-24 and #10-32 mounting screws, Cage Nut Mounting Kit, Velcro Strap, Fiber Optic Warning Label"

EDGE™ Housing 2 rack unit, Gray, holds up to 24 EDGE modules or panels



Ordering Information	
Shipping Weight	10.9 kg
Module Capacity	24
Width	432 mm (17.01 in)
Height Unit	2 U
Units per Delivery	1/1
Trunk Capacity	24 (size 1 or 2, double stack cradle)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.