


EMT Straps

Snap-On Type - One Hole - Steel



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
511	15610	1/2"	100	1000	25	1.79	.57
512	15620	3/4"	100	1000	30	1.96	.62
513	15630	1"	50	500	25	2.25	.75
514	15640	1-1/4"	25	250	20	2.85	.88
515	15650	1-1/2"	10	100	12	3.16	.99
516	15660	2"	10	100	16	3.93	1.10
517*	15670	2-1/2"	---	50	21	5	1.28
518*	15680	3"	---	25	12	5.55	1.28
519*	15690	3-1/2"	---	25	17	6.37	1.28
520*	15700	4"	---	25	17	6.87	1.28

*EMT and Rigid

Features

- Snap-on type EMT strap with one hole
- Inverted rib for strength
- Easy to install

Applications

- Indoor or outdoor use
- Use to support EMT conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel


Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FBI-2014

Snap-On Type - Two Hole - Steel



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
521	14950	1/2"	50	500	10	2.25	.70
522	14960	3/4"	50	500	10	2.75	.92
523	14970	1"	50	500	15	3	1.16
524	14980	1-1/4"	20	200	12	3.75	1.51
525	14990	1-1/2"	20	200	16	4.25	1.74
526	15000	2"	---	50	7	4.81	2.21
527*	15010	2-1/2"	---	25	4	5.87	1.43
528*	15020	3"	---	25	5	6.50	1.75
529*	15030	3-1/2"	---	25	7	7.12	2
530*	15040	4"	---	25	7	7.75	2.25

*EMT and Rigid

Features

- Snap-on type EMT strap with two holes
- Greater load bearing capability
- Easy to install

Applications

- Indoor or outdoor use
- Use to support EMT conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FBI-2014