




Our latest pin-based LED retrofits are perfect for PL applications, and provide a long-lasting LED alternative for walls or recessed areas in offices, hotels, lobbies, schools, etc.

2-PIN


Compatible bases



OR

4-PIN

Compatible bases



HORIZONTAL

OMNI-DIRECTIONAL

VERTICAL



7W

LED-7311-G3

Replaces up to 13W

G23-2 base

7W

LED-7312-G3

Replaces up to 13W

GX23-2 base

7W

LED-7322-G3

Replaces up to 26W

G24d base

NEW!

11W

LED-7324-G3

Replaces up to 26W

G/GX24q base

11W

LED-7334-G3

Replaces up to 26W

G/GX24q base



5W

LED-7300

Replaces up to 13W
GX23 base



10W

LED-7320-G3

Replaces up to 42W
G/GX24q base

NEW!



10W

LED-7330

Replaces up to 26W

G/GX24q base

Type B Only



23W

LED-7340

Replaces up to 42W
2G11 base



7W

LED-7310-G3

Replaces up to 32W
G24d/q base


NEW!



25W

LED-7342

Replaces up to 42W
G24q base



Type A/B



Type A



12W

LED-7318

Replaces up to 26W
G/GX24q base



12W

LED-7338

Replaces up to 26W
G/GX24q base

Type A = Ballast Compatible
Type A/B = Ballast Bypass 120-277V or Ballast Compatible
Type B = Ballast Bypass

telescoping horizontal & fixed vertical adapter included w/ each lamp



Also Available

LED-7319

Extender for 7318 and 7338

SPECIFICATIONS

DESCRIPTION	MODEL #	LUMENS	REPLACES	LED POWER	BASE	BEAM ANGLE	CCT	DIMENSIONS
LED-7300 5W 2-PIN UNIVERSAL / TYPE A+B	LED-7300-27K-G2	500	13W	5W	GX23	360°	2700K	5.5" x 1.4"
	LED-7300-35K-G2	550					3500K	
	LED-7300-40K-G2	550					4000K	
	LED-7300-50K-G2						5000K	
LED-7310 5W 2-PIN & 4-PIN UNIVERSAL / TYPE B	LED-7310-27K-G3	890	32W	7W	G24d/q	360°	2700K	5.5" x 1.4"
	LED-7310-35K-G3	949					3500K	
	LED-7310-40K-G3	970					4000K	
	LED-7310-50K-G3	990					5000K	
LED-7311 7W 2-PIN UNIVERSAL / TYPE A+B	LED-7311-27K-G3	815	13W	7W	G23-2	120°	2700K	5.8" x 1.4"
	LED-7311-35K-G3	883					3500K	
	LED-7311-40K-G3	892					4000K	
	LED-7311-50K-G3						5000K	
LED-7312 7W 2-PIN UNIVERSAL / TYPE A+B	LED-7312-27K-G3	801	13W	7W	GX23-2	120°	2700K	5.8" x 1.4"
	LED-7312-35K-G3	899					3500K	
	LED-7312-40K-G3	914					4000K	
	LED-7312-50K-G3						5000K	
LED-7318 12W 4-PIN UNIVERSAL / TYPE A+B	LED-7318-27-A	837	26W	12W	G/GX24q	120°	2700K	3.8" x 3"
	LED-7318-35-A	1157					3500K	
	LED-7318-40-A	1198					4000K	
LED-7319 12W 4-PIN UNIVERSAL / TYPE A+B	LED-7319	Extender for 7318 and 7338		G24q/d				
LED-7320 10W 4-PIN UNIVERSAL / TYPE A+B	LED-7320-27K-G3	1350	42W	10W	G/GX24q	360°	2700K	6.2" x 1.4"
	LED-7320-35K-G3	1550					3500K	
	LED-7320-40K-G3	1600					4000K	
	LED-7320-50K-G3	1635					5000K	
LED-7322 7W 2-PIN UNIVERSAL / TYPE A+B	LED-7322-27K-G3	849	26W	7W	G24d	120°	2700K	5.8" x 1.4"
	LED-7322-35K-G3	869					3500K	
	LED-7322-40K-G3	887					4000K	
	LED-7322-50K-G3						5000K	
LED-7324 11W 4-PIN UNIVERSAL / TYPE A+B	LED-7324-27K-G3	1050	42W	11W	G/GX24q	360°	2700K	5.6" x 1.3"
	LED-7324-35K-G3	1125					3500K	
	LED-7324-40K-G3	1200					4000K	
	LED-7324-50K-G3	1200					5000K	
LED-7330 10W 4-PIN BALLAST COMPATIBLE / TYPE A	LED-7330-27K-G2	760	26W	10W	G/GX24q	360°	2700K	6.2" x 1.4"
	LED-7330-35K-G2	850					3500K	
	LED-7330-40K-G2	916					4000K	
LED-7334 11W 4-PIN BALLAST COMPATIBLE / TYPE A	LED-7334-27K-G3	974	26W	11W	G/GX24q	120°	2700K	5.8" x 1.4"
	LED-7334-35K-G3	1057					3500K	
	LED-7334-40K-G3	1014					4000K	
LED-7338 12W 4-PIN BALLAST COMPATIBLE / TYPE A	LED-7338-27-A	1100	26W	12W	G/GX24q	120°	2700K	3.8" x 3"
	LED-7338-35-A	1100					3500K	
	LED-7338-40-A	1100					4000K	
LED-7340 23W 4-PIN BALLAST BYPASS / TYPE B	LED-7340-30K-G2	2100	40W	17W	2G11	160°	42W	22" x 1.6"
	LED-7340-35K-G2	2100					42W	
	LED-7340-40K-G2	2200					42W	
LED-7342 25W 4-PIN BALLAST BYPASS / TYPE B	LED-7342-27K-G2	2000	42W	25W	G24q	140°	2700K	4.2" x 3.6"
	LED-7342-35K-G2	2500					3500K	
	LED-7342-40K-G2	2500					4000K	
LED-7356-SP 40W PAR 56 LAMP	LED-7356-SP30	3500	300W	40W	GX16d	15°	3000K	7" x 7" x 5"
	LED-7356-SP40						4000K	8" x 7" x 5"
	LED-7356-SP50						5000K	9" x 7" x 5"
LED-7356-NF 40W PAR 56 LAMP	LED-7356-NF30	3500	300W	40W	GX16d	25°	3000K	10" x 7" x 5"
	LED-7356-NF40						4000K	11" x 7" x 5"
	LED-7356-NF50						5000K	12" x 7" x 5"
LED-7356-FL 40W PAR 56 LAMP	LED-7356-FL30	3500	300W	40W	GX16d	40°	3000K	13" x 7" x 5"
	LED-7356-FL40						4000K	14" x 7" x 5"
	LED-7356-FL50						5000K	15" x 7" x 5"

VOLTAGE: 120-277VAC • -80 CRI • 50,000 HOUR RATED LIFE • 5 YEAR WARRANTY



PAR 56 LAMPS

- ▶ Available in three different beam angles – Spot, Narrow Flood and Flood
- ▶ Forward-phase, line voltage dimmable
- ▶ Suitable for damp locations

40W

LED-7356-SP
LED-7356-NF
LED-7356-FL

Replaces up to 300W Halogen
GX16d base

