

SHOE BOX + WALL PACK



7 MODELS REPLACING UP TO 1000W HID. Retrofit almost any shoe box or wall pack fixture to energy & maintenance saving LED technology. Eliminates ballast failures. FlexColor on several models allows for less stocked inventory as well as field adjustability. Larger models include support feet to prevent socket sag.



**LED PANEL
ADHERES TO
FITTURE LENS**

← - **FLEXCOLOR**

← - **ROTATABLE
BASES —
TO DIRECT LUMENS
OUT OF FITTURE**

LED-8091 ↗

← LED-8088



**120/
277V**

*



ACTIVE COOLING



CRI



ENCLOSED FIXTURES



-40°F TO 122°F

OPERATING TEMP



**DAMP
LOCATION**

ENVIRONMENT



L70

50,000hrs
RATED LIFE

* ALSO WORKS ON 208V & 240V.

120-277V PART #	347V PART #	REPLACES	WATTAGE	LUMENS	COLOR	BASE	DIMENSIONS	LISTINGS
BOLLARD + POST TOP BALLAST BYPASS TYPE B								
LED-8029E345-A-FW	LED-8029E345C-A-FW	70W/100W/150W	FLEXWATT 12W/ 18W /24W	1550-3360	FLEXCOLOR 3000K/ 4000K /5000K	E26	3.0" x 6.6"	
LED-8029M345-A-FW	LED-8029M345C-A-FW					EX39	3.0" x 6.9"	
LED-8024E345-G7-FW	LED-8024E345C-G7-FW	175W/250W/320W	FLEXWATT 35W/ 45W /60W	5140-8870		E26	3.4" x 7.4"	
LED-8024M345-G7-FW	LED-8024M345C-G7-FW					EX39	3.4" x 7.8"	
LED-8027M345-G7-FW	LED-8027M345C-G7-FW	320W/400W	FLEXWATT 80W/ 100W /110W	11370-15730		EX39	3.8" x 9.5"	
HV LED-8027M345-G7-FW-HV*								
LED-8037E345-A	LED-8037E345C-A	50W	11W	1550/ 1610 /1650	FLEXCOLOR 3000K/ 4000K /5000K	E26	2.6" x 5.3"	
LED-8038E345-A	LED-8038E345C-A	70W	14W	1850/ 1950 /1990		E26	2.6" x 5.3"	
LED-8039E345D-A	LED-8039E345C-A	100W	18W	2450/ 2560 /2610		E26	2.6" x 6.3"	
LED-8039M345D-A	LED-8039M345C-A	100W	18W	2450/ 2560 /2610		EX39	2.6" x 7.0"	
LED-8033E30D-G7		175W	35W	5140	3000K	E26	3.4" x 7.2"	
LED-8033E40D-G7				5290	4000K			
LED-8033E50D-G7				5360	5000K			
LED-8033M30D-G7				5140	3000K	EX39	3.4" x 7.8"	
LED-8033M40D-G7				5290	4000K			
LED-8033M50D-G7				5360	5000K			

DEFAULT WATTAGE AND CCT FOR SUPERFLEX LAMPS ARE SHOWN IN BOLD.

SUPERflex SWITCH BETWEEN COLOR TEMPS & WATTS

flexCOLOR SWITCH BETWEEN 3 COLOR TEMPS

SURGE ARRESTORS

PART #	DESCRIPTION	ENCLOSURE	NOM DIS CURRENT	STRIKE RATING	DIMENSIONS
SPD-277P-10KA-EC-1	10kA SURGE ARRESTOR, 120-277V, SERIES W/ THERMAL FUSE	ROUND IP65	10,000A	1@10kA, 2@6.5kA 15@3kA, 110@1.5kA	2.5" x 1.4"
SPD-347P-10KA	10kA SURGE ARRESTOR, 120-347V, SERIES W/ THERMAL FUSE	ROUND IP67			

STEP DOWN TRANSFORMERS

PART #	DESCRIPTION	MAX WATTAGE	NOM DISCHARGE CURRENT	THD	POWER FACTOR	DIMENSIONS
MTM04506224C-LW	450VA STEPDOWN TRANSFORMER	400W	480/347V IN / 277V OUT	3.4% / 3.8%	0.99	4.2" x 2.7" x 2.2"
MTM01606224C-LW	160VA STEPDOWN TRANSFORMER	140W		4.3% / 4.1%	0.99	4.2" x 2.0" x 1.6"
MTM00506224C-LW	50VA STEPDOWN TRANSFORMER	45W	480/347V IN / 240V OUT	6.2% / 6.7%	0.98 / 0.97	3.0" x 1.7" x 1.4"

