



Color: White

Weight: 7.1 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant Current
120V	0.25A
208V	0.15A
240V	0.13A
277V	0.12A
Input Watts	25.7-41.5W

LED Info

Watts	30W
Color Temp	Field Adjustable
Color Accuracy	79-81 CRI
L70 Lifespan	75,000 Hours
Lumens	3117-4802
Efficacy	106.6-127.5 lm/W

Technical Specifications**Field Adjustability****Field Adjustable:**

Field adjustable light output:
2' x 2': 25W/30W/40W (factory default 30W)
Color Temperature (selectable by 3500K, 4000K and 5000K)

Compliance**UL Listed:**

Suitable for damp locations

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PB45PSA0

Performance**Lifespan:**

75,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics**LEDs:**

Long-life, high-efficacy, surface-mount LEDs

Electrical**Driver:**

Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.25A, 208V: 0.15A, 240V: 0.13A, 277V: 0.12A

THD:

5.8% at 120V, 11.03% at 277V

Power Factor:

99.4% at 120V, 92.3% at 277V

Battery Backup:

Battery backup will operate the LED Lamp for 90 minutes if power fails. Wired for 120V-277V.

Construction**Ambient Operating Temperature:**

-30°C (-22°F) to 40°C (104°F)

Lens:

Frosted Polystyrene

Mounting:

Recessed ceiling

IC Rated:

Suitable for insulated ceilings

Technical Specifications (continued)

Construction

Housing:

Lightweight aluminum housing

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other


Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- Field-adjustable light output (3 discrete steps)
- White tunable (3 discrete color temperatures)
- Can be changed before, during or after installation
- 75,000-Hour LED lifespan

Ordering Matrix

Family	Size	Voltage	Options
EZPANFA	2X2	/D10	/E2
	1X4 = 1' x 4'	/D10 = 0-10V Dimming	Blank = No Option
	2X2 = 2' x 2'		/LC = Lightcloud® Controller
	2X4 = 2' x 4'		/LCS = Lightcloud® Sensor
			/E2 = Battery Backup