




# BC26 UNIVERSAL BEAM CLAMP WITH TAPPED HOLE



## FEATURES

One thru-hole for easier installation of threaded rod


## SPECIFICATIONS

| Catalog Number | Material  | Finish            | Rod Size(R S) | A      | Hole Size(H S) | Hole Type | Screw Diameter(Sc) | Torque(T Q) | Static Load 1(F1) | Static Load 2(F2) |
|----------------|-----------|-------------------|---------------|--------|----------------|-----------|--------------------|-------------|-------------------|-------------------|
| BC260025EG     | Cast Iron | Electrogalvanized | 1/4"          | 13/16" | 1/4"           | Threaded  | 1/4"               | 40 ft lb    | 250 lb            | 100 lb            |

## ADDITIONAL PRODUCT DETAILS

Setscrew must be tightened and torqued onto the sloped side of the I-beam.

## DIAGRAMS



**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

**Europe**

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

**Europe**

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

**APAC**

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**