

Commercial/Mechanical/Industrial Services Bronze, Carbon and Stainless Steel Ball Valves

The NIBCO® ball valve line is one of the most specified mechanical service lines in use today. Specifying engineers recognize our bronze two-piece ball valves by name and have made them the choice in building service and general utility service applications. These versatile valves are specified worldwide in applications such as:

- Hot and cold water
- Condenser and chilled water
- Hot water heating
- Low & medium pressure steam
- Fire protection control and trim & drain
- Compressed air
- Vacuum
- Natural and LP gas
- Medical gas systems
- Process piping

Why Engineers Specify NIBCO Ball Valves:

- Full Port—high flow coefficient, less pressure drop
- Conventional Port—non-critical flow requirements
- All valves have blowout proof stems
- Bronze valves are “Dezincification-Resistant”
- NIB-Seal® Insulated Extended Handle System
- Multiple design options and application specific features



To download the most current submittal sheet, go to:
www.nibco.com

T-560-BR-R20/Y20
T-560-BR-R66/Y66



600 PSI CWP
1-Piece Bronze Body
Reduced Port
Bronze Stem, Brass Ball or
SS Stem, SS Ball
PTFE/RPTFE Seat
Threaded Connection
MSS SP-110
1/4" - 2"

T/S-580-70



600 PSI CWP
150 PSI SWP
2-Piece Bronze Body
Conventional Port
Bronze Stem, Chrome
Plated Ball
Threaded or Solder
Connection
MSS SP-110
1 1/4" - 3"

T/S-580-70-66



600 PSI CWP
150 PSI SWP
2-Piece Bronze Body
Conventional Port
SS Stem, SS Ball
Threaded or Solder
Connection
MSS SP-110
1 1/4" - 3"

T/S-585-70



600 PSI CWP 150 PSI SWP
2-Piece Bronze Body
Full Port
Bronze Stem,
Chrome Plated Ball
Threaded or Solder
Connection
MSS SP-110
1/4" - 2"

T/S-585-70-66




600 PSI CWP 150 PSI SWP
2-Piece Bronze Body
Full Port
SS Stem, SS Ball
Threaded or Solder
Connection
MSS SP-110
1/4" - 2"

TS/ST-585-70



600 PSI CWP 150 PSI SWP
2-Piece Bronze Body
Full Port, Bronze Stem,
Chrome Plated Brass Ball
Threaded x Solder or
Solder x Threaded
Connection
MSS SP-110
1/2" - 2"

MTT-585-70



600 PSI CWP 150 PSI SWP
2-Piece Bronze Body
Full Port
Bronze Stem, Chrome
Plated Brass Ball
Male x Female Threaded
End Connection
MSS SP-110
1/2" - 2"

T-585-70-CP



600 PSI CWP
2-Piece Bronze Body w/
Chrome Plating
Full Port
Bronze Stem, Chrome
Plated Brass Ball
Threaded Connection
MSS SP-110
1/2" - 2"

T/S/PS-585-70-HC/66-HC



600 PSI CWP
2-Piece Bronze Body
Full Port
Bronze Stem,
Chrome Plated Brass Ball or
SS Stem, SS Ball
Threaded, Solder or
Tube End Press Connection
Rated to 200 PSI
MSS SP-110
1/2" - 3/4"
Hose Cap and Chain

T/S-585-70-SU



600 PSI CWP 150 PSI SWP
2-Piece Bronze Body
Full Port
Bronze Stem
Chrome Plated Brass Ball
Thrd x Thrd, S x S, Thrd x S,
S x Thrd Connections
MSS SP-110
1/2" - 2"
Single Union

T-585-70-66-ST



600 PSI CWP 250 PSI SWP
2-Piece Bronze Body
Full Port
SS Stem, SS Ball
Threaded Connection
MSS SP-110
1/2" - 2"
Carbon-filled PTFE seats

PS-585-70/-66



200 PSI CWP
Max Operating Temp. 250°F
2-Piece Bronze Body
Full Port, Bronze Stem
Chrome Plated Brass Ball
or SS Stem, SS Ball
Tube End Press Connection
MSS SP-110
1/2" - 2"