



Legrand

Heavy-Duty Spec Grade Receptacles, Back & Side Wire, 20A, 250V, White
Part No. 5862W

Heavy-Duty Spec Grade Duplex Receptacle Back & Side Wire 20amp 250volt Black



Features & Benefits

Heavy-duty, brass strap for added strength and ground conductivity.

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Strap tabs wrap around face to prevent strap from separating from face and back body.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

High strength nylon face.

Internal screw-pressure-plate back and side wired to accept #14 and #10 AWG stranded or solid copper or copper-clad conductors.

Eight back wire holes.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

Specifications

General Info

Color White

UPC Number 785007998405

Countries Of Origin Mexico

Product Line Pass & Seymour

Application Sector Commercial

Standard cULus UL498, CSA C22.2 No. 42

Listing Agencies / 3rd Party Agencies

cULus Listed Yes

cULus ListingNumber 140596

Technical Information

Number of Poles Double Pole

Voltage	250 V
Connection	Back and side wire
Dielectric Strength	Withstands 2000V minimum
Temperature Rating	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current, Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact
Wire Size	#14 - #10
Number of Wires	3
Environmental Conditions	Flammability: UL94 V2
